



**Now a
5 Year
Warranty**

PREMIER

8.5' Widebody Gooseneck/ Fifthwheel Race Trailer

Specifications vary by plant



STANDARD FEATURES

Shown with Optional Equipment

- Tube Main Frame Construction
- 16" O.C. Frame
- 16" O.C. Tube Sidewalls
- 16" O.C. Roof Bows
- Torsion Axles
- EZ-Lube Hubs
- Electric Brakes
- Radial Tires
- (2) Speed Landing Gear
- Enclosed Landing Gear
- 3/4" High Performance Floor
- High Performance Wall Liner
- White Vinyl Insulated Ceiling Liner
- .040 Screwless Aluminum Exterior
- Two Tone Exterior Available No Charge
- Stainless Steel Front Insert
- Stainless Steel Front Corners
- Stainless Steel Rear Corners and Header
- (1) Piece Aluminum Roof
- Truck Body Extrusion
- Heavy Duty Ramp Door with Spring Assist & 16" Ramp Door Extension
- Recessed Horizontal Cam Lock on Ramp Door
- 48" Heavy Duty Entry Door with Flushlock and Aluminum Slide-Out Step
- Front ATP Access Door
- (1) Non-Powered Vent
- 7-Way Plug
- LED Tail Lights
- LED Clearance Lights
- Back-Up Lights
- (2) Deluxe Dome Lights and Switch
- Beavertail
- (4) 5000# Recessed Bolted D-Rings
- Automotive Undercoating
- Limited 5 Year Warranty

IN: 877 475 5665 • TX: 866 622 0858 • AZ: 877 541 5665 • UT: 877 544 5665 • PA: 844 661 5665

LOOK Trailers is a family-focused company; building industry-leading products while making safety, innovation and customer service our highest priorities.

| | PREMIER GOOSENECK RACE TRAILER | | | |
|-------------------------|---------------------------------------|-----------------------|-----------------------|-----------------------|
| | PLRTG8.5X36RE3 | PLRTG8.5X40RE4 | PLRTG8.5X44RE4 | PLRTG8.5X48RE4 |
| Overall Length | 36'6" | 40'6" | 44'6" | 48'6" |
| Width | 102" | 102" | 102" | 102" |
| Height | 102" | 104" | 104" | 104" |
| Interior Length | 36'4" | 40'4" | 44'4" | 48'4" |
| Interior Width | 96" | 96" | 96" | 96" |
| Interior Height | 78" | 78" | 78" | 78" |
| Platform Height | 23" | 25" | 25" | 25" |
| Rear Opening Height | 75" | 75" | 75" | 75" |
| Rear Opening Width | 96" | 96" | 96" | 96" |
| Gooseneck Ball Size | 2 5/16" | 2 5/16" | 2 5/16" | 2 5/16" |
| Brakes | ELECTRIC | ELECTRIC | ELECTRIC | ELECTRIC |
| GVWR | 15,000# | 18,000# | 18,000# | 18,000# |
| Curb Weight | 7550# | 8000# | 8600# | 9240# |
| Payload Capacity | 7450# | 10,000# | 9400# | 8760# |
| Tires | ST225/75R15 | ST235/80R16 | ST235/80R16 | ST235/80R16 |
| Wheels | E-COAT | E-COAT | E-COAT | E-COAT |
| Frame | TUBE | TUBE | TUBE | TUBE |
| Exterior | .040 Screwless | .040 Screwless | .040 Screwless | .040 Screwless |
| One Piece Aluminum Roof | STD | STD | STD | STD |
| Floor | 3/4" | 3/4" | 3/4" | 3/4" |
| Sidewalls | High Performance | High Performance | High Performance | High Performance |
| Ceiling | Insul. White Vinyl | Insul. White Vinyl | Insul. White Vinyl | Insul. White Vinyl |
| Tail Lights | LED | LED | LED | LED |
| Clearance Lights | LED | LED | LED | LED |
| Dome Light | 2 | 2 | 2 | 2 |
| Switch | STD | STD | STD | STD |
| Side Door | 48" Heavy Duty | 48" Heavy Duty | 48" Heavy Duty | 48" Heavy Duty |
| Ramp | STD | STD | STD | STD |
| Crossmembers | 16" OC | 16" OC | 16" OC | 16" OC |
| Side Posts | 16" OC | 16" OC | 16" OC | 16" OC |
| Roof Bows | 16" OC | 16" OC | 16" OC | 16" OC |
| Axles | TORSION | TORSION | TORSION | TORSION |
| EZ Lube | YES | YES | YES | YES |
| Undercoat | Automotive | Automotive | Automotive | Automotive |

Specifications Subject to Change Without Notice