

	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12	
Model #	K8412MHFB-100	K8414MHFB-	K8416MHFB-	K8418MHFB-	K8420MHFB-	K10212MHFB-100	
CAPACITIES		100	100	100	100		
			_				
GVWR (lbs)	9900						
GAWR (lbs/axle)	5000						
CHASSIS							
Frame	6" x 2" Steel Tube						
Tongue			6" Extension, 6" x	2" Steel Triple Tul	oe .		
Crossmembers			Formed Steel	, 16" On-Center			
Integrated Step(s)						Interior Recessed	
Coupler			2-5/16" .	Adjustable			
Safety Chains			DOT C	ompliant			
Tongue Jack			7K Drop Lo	eg, Set-Back			
Wall Studs			Steel Tube,	16" On-Center			
Roof Bows		Steel Tube, 8" On-Center					
Stabilizers			Rear Drop	-Leg Jacks			
Rear Door		Barn-	Style Double with	Cambar and Step	Bumper		
Side Door	3	6" Wide Flush Locl	k, Additional Barlo	ck and Hasp, Cas	t Aluminum Holdba	ack	
Vents	Roof Vent Frame, Salem Sidewall Airflow						
Fenders	Smooth Aluminum						
Axle	(2) 5200 lb. Torsion Brake						
Hubs		Easy Lube					
Breakaway		Battery, Switch, and Lanyard					
Tires		ST225/75R15D 8-PR					
Wheels			15", 6-H	lole Steel			
Exterior Finish			.030" A	luminum			
Undercoating				motive			
Exterior Fastening			VHB Bonde	d (Screwless)			
Exterior Trim	2.5" Top E	xtrusion, 3" Bottor	n Extrusion, ATP F	Radius Front Corne	ers, Color Matching	g Rear Hoop	
Stone Guard			24'	' ATP			
Roof			Flat Top Sean	nless Aluminum			
Roof Cap			T	PO			
Exterior Storage	(4) Heavy Duty L	adder Racks with I	Rear Roller	' ' ' ' '	adder Racks with Roller	(4) Heavy Duty Ladder Racks with Rear Roller	
Exterior Accessories		ATP and Eng	ineered Wood Tor	igue Cover, Front A	Access Ladder		
Interior Walls			Enginee	red Wood			
Interior Trim			Engineered Woo	d Wall Transitions	:		
Flooring			3/4" Engin	eered Wood			
Interior Lights		(2) 48" 110V Wrap	Around LED, (2) L	ED		





	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12		
Switches		(1) 110V, (1) Dome Light, 12V, (1) Pair Top Fuel 3-Way, 12V						
Fixtures	(3) Tool Cabinets with Aluminum Work Station	· '	ts with Aluminum Station	` '	s with Aluminum Station	(3) Tool Cabinets with Aluminum Work Station		
Cargo Control		(4) 5000 lb. Recessed D-Rings, Recessed Wall E-Track, One Row						
Connector Plug		Round 7-pin Blade						
Exterior Lights	(2	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights						
110v Electrical	(1) Exterior GFI Recep	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles						





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20				
Model #	K10214MHFB-100	K10216MHFB-100	K10218MHFB-100	K10220MHFB-100				
CAPACITIES								
GVWR (lbs)		99	00					
GAWR (Ibs/axle)			00					
CHASSIS								
rame		6" x 2" S	teel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube							
Crossmembers		Formed Steel,	16" On-Center					
ntegrated Step(s)		Interior I	Recessed					
Coupler		2-5/16" <i>A</i>	djustable					
Safety Chains		DOT Co	mpliant					
ongue Jack		7K Drop Le	g, Set-Back					
Wall Studs		Steel Tube, 1	6" On-Center					
Roof Bows		Steel Tube,	8" On-Center					
Stabilizers		Rear Drop	-Leg Jacks					
Rear Door		Barn-Style Double with (Cambar and Step Bumper					
Side Door	36" Wic	le Flush Lock, Additional Barlo	ck and Hasp, Cast Aluminum H	loldback				
/ents	Roof Vent Frame, Salem Sidewall Airflow							
enders	Smooth Aluminum							
Axle	(2) 5200 lb. Torsion Brake							
lubs	Easy Lube							
Breakaway	Battery, Switch, and Lanyard							
Tires	ST225/75R15D 8-PR							
Wheels	15", 6-Hole Steel							
Exterior Finish	.030" Aluminum							
Undercoating	Automotive							
Exterior Fastening			(Screwless)					
Exterior Trim	2.5" Top Extrusi	on, 3" Bottom Extrusion, ATP R		tching Rear Hoop				
Stone Guard			ATP					
Roof		·	less Aluminum					
Roof Cap	/A) II		20	B 1 W B - "				
Exterior Storage		Racks with Rear Roller		Racks with Rear Roller				
Exterior Accessories		ATP and Engineered Wood Ton	-	PF				
nterior Walls			red Wood					
nterior Trim		•	l Wall Transitions					
Flooring		-	eered Wood					
Interior Lights			Around LED, (2) LED					
Switches	(0) Tool Oaking to will		(1) Pair Top Fuel 3-Way, 12V	Aluminum Warls Otalian				
Fixtures		Aluminum Work Station	. ,	Aluminum Work Station				
Cargo Control	(-	4) 5000 lb. Recessed D-Rings,	kecessed Wall E-Track, One Ro)W				





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20		
Connector Plug		Round 7	pin Blade			
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
110v Electrical	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior					
i i ov Licotiicai	Receptacles					





	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12		
Model #	K8412MHFB-070	K8414MHFB-	K8416MHFB-	K8418MHFB-	K8420MHFB-	K10212MHFB-070		
Wouei #	K0412WITFD-070	070	070	070	070	K10212MHFB-070		
CAPACITIES								
GVWR (lbs)			7(000				
GAWR (lbs/axle)		3500						
CHASSIS								
Frame			6" x 2" S	Steel Tube				
Tongue			6" Extension, 6" x	2" Steel Triple Tul	oe .			
Crossmembers			Formed Steel	, 16" On-Center				
Integrated Step(s)						Interior Recessed		
Coupler			2-5/16" /	Adjustable				
Safety Chains			DOT Co	ompliant				
Tongue Jack			7K Drop Le	eg, Set-Back				
Wall Studs			Steel Tube,	16" On-Center				
Roof Bows			Steel Tube,	8" On-Center				
Front Profile				ound				
Stabilizers				-Leg Jacks				
Rear Door			Style Double with	•	-			
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback							
Vents	Roof Vent Frame, Salem Sidewall Airflow							
Fenders	Smooth Aluminum							
Axle	(2) 3500 lb. Torsion Brake							
Hubs		Easy Lube						
Breakaway		Battery, Switch, and Lanyard ST205/75R15C 6-PR						
Tires			· · · · · · · · · · · · · · · · · · ·					
Wheels			· · · · · · · · · · · · · · · · · · ·	lole Steel				
Exterior Finish				luminum				
Undercoating				motive				
Exterior Fastening Exterior Trim	2 5" Ton E	vtrucion 2" Potton		d (Screwless)	ers, Color Matching	ı Door Hoon		
Stone Guard	2.3 TOP E	xtrusion, 3 Botton		'ATP	ers, Color Matching	j Keai Hoop		
Roof				nless Aluminum				
Roof Cap			•	PO				
Exterior Storage	(4) Heavy Duty I	adder Racks with I		(5) Heavy Duty L	adder Racks with	(4) Heavy Duty Ladder		
_	(1) 110011				Roller	Racks with Rear Roller		
Exterior Accessories		ATP and Eng	ineered Wood Ton		Access Ladder			
Interior Walls				red Wood				
Interior Trim			-	d Wall Transitions				
Flooring			3/4" Engin	eered Wood				





	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12		
Interior Lights		(2) 48" 110V Wrap Around LED, (2) LED						
Switches		(1) 110V, (1) Dome Light, 12V, (1) Pair Top Fuel 3-Way, 12V						
Fixtures	(3) Tool Cabinets with Aluminum Work Station	` '	s with Aluminum Station	` ,	ets with Aluminum Station	(3) Tool Cabinets with Aluminum Work Station		
Cargo Control		(4) 5000 lb. Recessed D-Rings, Recessed Wall E-Track, One Row						
Connector Plug	Round 7-pin Blade							
Exterior Lights	(2	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights						
110v Electrical	(1) Exterior GFI Recep	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles						





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20				
Model #	K10214MHFB-070	K10216MHFB-070	K10218MHFB-070	K10220MHFB-070				
CAPACITIES								
GVWR (lbs)		70	00					
GAWR (lbs/axle)			00					
CHASSIS								
		۲" y 2" C	tool Tubo					
Frame Tongue	6" x 2" Steel Tube 6" Extension, 6" x 2" Steel Triple Tube							
Crossmembers		•	16" On-Center					
Integrated Step(s)		Interior F						
Coupler			djustable					
Safety Chains			mpliant					
Tongue Jack			g, Set-Back					
Wall Studs		•	6" On-Center					
Roof Bows		·	B" On-Center					
Front Profile		·	und					
Stabilizers		Rear Drop	Leg Jacks					
Rear Door		Barn-Style Double with (Cambar and Step Bumper					
Side Door	36" Wid	le Flush Lock, Additional Barlo	ck and Hasp, Cast Aluminum F	loldback				
V ents	Roof Vent Frame, Salem Sidewall Airflow							
Fenders	Smooth Aluminum							
Axle	(2) 3500 lb. Torsion Brake							
lubs	Easy Lube							
Breakaway	Battery, Switch, and Lanyard							
Tires	ST205/75R15C 6-PR							
Wheels	15", 5-Hole Steel							
Exterior Finish	.030" Aluminum							
Undercoating	Automotive							
Exterior Fastening			(Screwless)					
Exterior Trim	2.5" Top Extrusi	on, 3" Bottom Extrusion, ATP R		tching Rear Hoop				
Stone Guard			ATP					
Roof		•	less Aluminum					
Roof Cap	(4) Haarin Berte Le II		(5) Haarin Britis Laddar	. Danka milik Dana Dalla				
Exterior Storage	,, , ,	Racks with Rear Roller	· · · · · ·	Racks with Rear Roller				
Exterior Accessories		ATP and Engineered Wood Ton	•	? r				
Interior Walls			red Wood					
Interior Trim			I Wall Transitions					
Flooring			eered Wood Around LED, (2) LED					
Interior Lights Switches		• •	(2) LED (1) Pair Top Fuel 3-Way, 12V					
Switches Fixtures	(2) Tool Cabinate with	(1) 110V, (1) Dome Light, 12V Aluminum Work Station		Aluminum Work Station				
FIALUI CO	(Z) TOOL CADILLETS WITH	MIGHINION WOLK STATION	(4) Tool Cabillets With	Aluminum Work Station				





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20		
Cargo Control	(4)	5000 lb. Recessed D-Rings,	Recessed Wall E-Track, One Ro	W		
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
110v Electrical	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles					

