

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
Model #	K10220PRFBRT-140	K10222PRFBRT-140	K10224PRFBRT-140	K10226PRFBRT-140	K10228PRFBRT-140	K10230PRFBRT-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	6000			7000		
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	12" Extension, 8" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	32"					48"
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
Vents	(1) Manual Roof, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 7000 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Aluminum					
Exterior Finish	.040" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
Stone Guard	24" ATP					
Rear Spoiler	6" Stainless Steel Flare with Taper					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Stainless Steel					
Interior Walls	Aluminum Overlay, Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) 11" LED					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
HVAC	Bracing and Wire for HVAC					

	8.5 x 32	8.5 x 34
Model #	K10232PRFBRT-140	K10234PRFBRT-140
CAPACITIES		
GVWR (lbs)	14000	
GAWR (lbs/axle)	7000	
CHASSIS		
Frame	8" x 2" Steel Tube	
Tongue	12" Extension, 8" x 2" Steel Triple Tube	
Crossmembers	Formed Steel, 16" On-Center	
Coupler	2-5/16" Adjustable	
Safety Chains	DOT Compliant	
Tongue Jack	7K Drop Leg, Set-Back	
Wall Studs	Steel Tube, 16" On-Center	
Roof Bows	Steel Tube, 16" On-Center	
Front Profile	Flat	
Beavertail	48"	
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist	
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback	
Vents	(1) Manual Roof, Sidewall Airflow	
Fenders	Extruded Aluminum	
Axle	(2) 7000 lb. Torsion Brake, Spread Axle Configuration	
Hubs	Easy Lube	
Breakaway	Battery, Switch, and Lanyard	
Tires	ST235/80R16E 10-PR	
Wheels	16", 8-Hole Aluminum	
Exterior Finish	.040" Aluminum	
Undercoating	Automotive	
Exterior Fastening	VHB Bonded (Screwless)	
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop	
Stone Guard	24" ATP	
Rear Spoiler	6" Stainless Steel Flare with Taper	
Roof	Flat Top Seamless Aluminum	
Roof Cap	Stainless Steel	
Interior Walls	Aluminum Overlay, Engineered Wood	
Interior Trim	Extruded Aluminum Wall Transitions	
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves	
Flooring	3/4" Engineered Wood	
Interior Lights	(2) 11" LED	
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V	
Cargo Control	(4) 5000 lb. Recessed D-Rings	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 32

8.5 x 34

Connector Plug	Round 7-pin Blade
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights
HVAC	Bracing and Wire for HVAC

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10224PRFBRT-160	K10226PRFBRT-160	K10228PRFBRT-160	K10230PRFBRT-160	K10232PRFBRT-160	K10234PRFBRT-160
CAPACITIES						
GVWR (lbs)	16000					
GAWR (lbs/axle)	8000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	12" Extension, 8" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	12K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	48"					
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
Vents	(1) Manual Roof, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 8000 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Oil Bath					
Breakaway	Battery, Switch, and Lanyard					
Tires	215/75R17.5J 18-PR					
Wheels	17.5", 8-Hole Aluminum					
Exterior Finish	.040" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
Stone Guard	24" ATP					
Rear Spoiler	6" Stainless Steel Flare with Taper					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Stainless Steel					
Interior Walls	Aluminum Overlay, Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) 11" LED					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
HVAC	Bracing and Wire for HVAC					

	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10226PRFBRT-210	K10228PRFBRT-210	K10230PRFBRT-210	K10232PRFBRT-210	K10234PRFBRT-210
CAPACITIES					
GVWR (lbs)	21000				
GAWR (lbs/axle)	7000				
CHASSIS					
Frame	8" x 2" Steel Tube			8" x 2" Steel Tube	
Tongue	12" Extension, 8" x 2" Steel Triple Tube			12" Extension, 8" x 2" Steel Triple Tube	
Crossmembers	Formed Steel, 16" On-Center			Formed Steel, 16" On-Center	
Coupler	2-5/16" Adjustable			2-5/16" Adjustable	
Safety Chains	DOT Compliant			DOT Compliant	
Tongue Jack	12K Drop Leg, Set-Back			12K Drop Leg, Set-Back	
Wall Studs	Steel Tube, 16" On-Center			Steel Tube, 16" On-Center	
Roof Bows	Steel Tube, 16" On-Center			Steel Tube, 16" On-Center	
Front Profile	Flat			Flat	
Beavertail	48"			48"	
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist			16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist	
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback	
Vents	(1) Manual Roof, Sidewall Airflow				
Fenders	Extruded Aluminum			Extruded Aluminum	
Axle	(3) 7000 lb. Torsion Brake, Spread Axle Configuration			(3) 7000 lb. Torsion Brake, Spread Axle Configuration	
Hubs	Easy Lube			Easy Lube	
Breakaway	Battery, Switch, and Lanyard			Battery, Switch, and Lanyard	
Tires	ST235/80R16E 10-PR			ST235/80R16E 10-PR	
Wheels	16", 8-Hole Aluminum			16", 8-Hole Aluminum	
Exterior Finish	.040" Aluminum			.040" Aluminum	
Undercoating	Automotive			Automotive	
Exterior Fastening	VHB Bonded (Screwless)			VHB Bonded (Screwless)	
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop	
Stone Guard	24" ATP			24" ATP	
Rear Spoiler	6" Stainless Steel Flare with Taper			6" Stainless Steel Flare with Taper	
Roof	Flat Top Seamless Aluminum			Flat Top Seamless Aluminum	
Roof Cap	Stainless Steel			Stainless Steel	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Interior Walls	Aluminum Overlay, Engineered Wood			Aluminum Overlay, Engineered Wood	
Interior Trim	Extruded Aluminum Wall Transitions			Extruded Aluminum Wall Transitions	
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves				
Flooring	3/4" Engineered Wood			3/4" Engineered Wood	
Interior Lights	(2) 11" LED			(2) 11" LED	
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V	
Cargo Control	(4) 5000 lb. Recessed D-Rings			(4) 5000 lb. Recessed D-Rings	
Connector Plug	Round 7-pin Blade			Round 7-pin Blade	
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights	
HVAC	Bracing and Wire for HVAC			Bracing and Wire for HVAC	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	K10220PRFBRT-070	K10222PRFBRT-070	K10224PRFBRT-070	K10226PRFBRT-070
CAPACITIES				
GVWR (lbs)	7000			
GAWR (lbs/axle)	3500			
CHASSIS				
Frame	6" x 2" Steel Tube			
Tongue	12" Extension, 6" x 2" Steel Triple Tube			
Crossmembers	Formed Steel, 16" On-Center			
Coupler	2-5/16" Adjustable			
Safety Chains	DOT Compliant			
Tongue Jack	7K Drop Leg, Set-Back			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	32"	48"		
Ramp(s)	16" Extension with Bullnose Cap (Both Ramps), (2) Recessed Cam Locks, 4000 lb. with Assist			
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			
Vents	(1) Manual Roof, Sidewall Airflow			
Fenders	Extruded Aluminum			
Axle	(2) 3500 lb. Torsion Brake, Spread Axle Configuration			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST205/75R15C 6-PR			
Wheels	15", 5-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			
Stone Guard	24" ATP			
Rear Spoiler	6" Stainless Steel Flare with Taper			
Roof	Flat Top Seamless Aluminum			
Roof Cap	Stainless Steel			
Interior Walls	Aluminum Overlay, Engineered Wood			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) 11" LED			
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			
HVAC	Bracing and Wire for HVAC			

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
Model #	K10220PRFBRT-100	K10222PRFBRT-100	K10224PRFBRT-100	K10226PRFBRT-100	K10228PRFBRT-100	K10230PRFBRT-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Steel Tube				8" x 2" Steel Tube	
Tongue	12" Extension, 6" x 2" Steel Triple Tube				12" Extension, 8" x 2" Steel Triple Tube	
Crossmembers	Formed Steel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	32"	48"				
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
Vents	(1) Manual Roof, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 5200 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Aluminum					
Exterior Finish	.040" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
Stone Guard	24" ATP					
Rear Spoiler	6" Stainless Steel Flare with Taper					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Stainless Steel					
Interior Walls	Aluminum Overlay, Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) 11" LED					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



PREMIER RACE
PREMIER FLAT TOP FLAT FRONT 10K

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
HVAC	Bracing and Wire for HVAC					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 32	
Model #	K10232PRFBRT-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	12" Extension, 8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Coupler	2-5/16" Adjustable
Safety Chains	DOT Compliant
Tongue Jack	7K Drop Leg, Set-Back
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback
Vents	(1) Manual Roof, Sidewall Airflow
Fenders	Extruded Aluminum
Axle	(2) 5200 lb. Torsion Brake, Spread Axle Configuration
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST225/75R15D 8-PR
Wheels	15", 6-Hole Aluminum
Exterior Finish	.040" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop
Stone Guard	24" ATP
Rear Spoiler	6" Stainless Steel Flare with Taper
Roof	Flat Top Seamless Aluminum
Roof Cap	Stainless Steel
Interior Walls	Aluminum Overlay, Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) 11" LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 32

Connector Plug	Round 7-pin Blade
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights
HVAC	Bracing and Wire for HVAC