

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10224PRFBSRT-BP-210	K10226PRFBSRT-BP-210	K10228PRFBSRT-BP-210	K10230PRFBSRT-BP-210	K10232PRFBSRT-BP-210	K10234PRFBSRT-BP-210
CAPACITIES						
GVWR (lbs)	21000					
GAWR (lbs/axle)	7000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	6" Extension, 8" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	6K Hydraulic					
Wall Studs	Steel 3" x 1" Tube, 16" On-Center					
Roof Bows	Steel Tube, 12" On-Center					
Front Profile	Flat					
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
Side Door	60" Aluminum Pull-Out Step, 60" Wide Double Flush Lock, Cast Aluminum Holdback					
Access Doors	36" x 33" Generator					
Vents	(1) Manual Roof, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(3) 7000 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Aluminum					
Exterior Finish	.080" Composite					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
Stone Guard	24" ATP					
Rear Spoiler	6" Stainless Steel Flare with Taper					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Stainless Steel					
Exterior Accessories	Bogey Wheels					
Interior Walls	Aluminum Overlay, Engineered Wood					
Interior Trim	36" Carpet Wall Liner, Extruded Aluminum Wall Transitions					
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood, Black Rubber Tread Overlay					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Interior Lights	(10) 11" LED					
Switches	(3) Pair Top Fuel 3-Way, 12V					
Fixtures	24" Full-Height Wardrobe, L-Shaped Base Cabinet, L-Shaped Overhead Cabinet, Storage Loft					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Interior Accessories	8' Removable Wall-Mount Ladder					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) 22" Rear Ramp LED Loading, (6) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
Hydraulic Components	14' 4-Post Auto Lift			16' 4-Post Auto Lift		
12v Electrical	12 Volt DC 24 Battery, Stereo with 4 Speakers, Subwoofer, USB Port and Receptacle					
110v Electrical	(1) Exterior GFI Receptacle, (4) Interior Receptacles, 50 Amp Motor Base Plug, 50 Amp Power Converter, 50 Amp Power Cord, 50 Amp Service Panel, Air Compressor Prep, Generator Prep with Transfer Switch					
HVAC	Bracing and Wire for HVAC					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 34
Model #	K10224PRFBSRT-BP-240	K10226PRFBSRT-BP-240	K10228PRFBSRT-BP-240	K10234PRFBSRT-BP-240
CAPACITIES				
GVWR (lbs)	24000			
GAWR (lbs/axle)	8000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	6" Extension, 8" x 2" Steel Triple Tube			
Crossmembers	Formed Steel, 16" On-Center			
Coupler	2-5/16" Adjustable			
Safety Chains	DOT Compliant			
Tongue Jack	6K Hydraulic			
Wall Studs	Steel 3" x 1" Tube, 16" On-Center			
Roof Bows	Steel Tube, 12" On-Center			
Front Profile	Flat			
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist			
Side Door	60" Aluminum Pull-Out Step, 60" Wide Double Flush Lock, Cast Aluminum Holdback			
Access Doors	36" x 33" Generator			
Vents	(1) Manual Roof, Sidewall Airflow			
Fenders	Extruded Aluminum			
Axle	(3) 8000 lb. Torsion Brake, Spread Axle Configuration			
Hubs	Oil Bath			
Breakaway	Battery, Switch, and Lanyard			
Tires	215/75R17.5J 18-PR			
Wheels	17.5", 8-Hole Aluminum			
Exterior Finish	.080" Composite			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			
Stone Guard	24" ATP			
Rear Spoiler	6" Stainless Steel Flare with Taper			
Roof	Flat Top Seamless Aluminum			
Roof Cap	Stainless Steel			
Exterior Accessories	Bogey Wheels			
Interior Walls	Aluminum Overlay, Engineered Wood			
Interior Trim	36" Carpet Wall Liner, Extruded Aluminum Wall Transitions			
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood, Black Rubber Tread Overlay			
Interior Lights	(10) 11" LED			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 34
Switches	(3) Pair Top Fuel 3-Way, 12V			
Fixtures	24" Full-Height Wardrobe, L-Shaped Base Cabinet, L-Shaped Overhead Cabinet, Storage Loft			
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Interior Accessories	8' Removable Wall-Mount Ladder			
Connector Plug	Round 7-pin Blade			
Exterior Lights	(2) 22" Rear Ramp LED Loading, (6) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			
Hydraulic Components	14' 4-Post Auto Lift		16' 4-Post Auto Lift	
12v Electrical	12 Volt DC 24 Battery, Stereo with 4 Speakers, Subwoofer, USB Port and Receptacle			
110v Electrical	(1) Exterior GFI Receptacle, (4) Interior Receptacles, 50 Amp Motor Base Plug, 50 Amp Power Converter, 50 Amp Power Cord, 50 Amp Service Panel, Air Compressor Prep, Generator Prep with Transfer Switch			
HVAC	Bracing and Wire for HVAC			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.