

	8.5 x 16	8.5 x 18	8.5 x 20
<b>Model #</b>	K10216STSVCH-070	K10218STSVCH-070	K10220STSVCH-070
<b>CAPACITIES</b>			
<b>GVWR (lbs)</b>		7000	
<b>GAWR (lbs/axle)</b>		3500	
<b>CHASSIS</b>			
<b>Tongue</b>	6" x 2" Steel Triple Tube		
<b>Crossmembers</b>	Formed Steel, 16" On-Center		
<b>Integrated Step(s)</b>	Interior Recessed		
<b>Coupler</b>	2-5/16" A-Frame		
<b>Safety Chains</b>	DOT Compliant		
<b>Tongue Jack</b>	2K Coupler Mounted		
<b>Wall Studs</b>	Steel Tube, 24" On-Center		
<b>Roof Bows</b>	Steel Tube, 24" On-Center		
<b>Front Profile</b>	V-Nose		
<b>Beavertail</b>	32"		48"
<b>Ramp(s)</b>	4000 lb. with Assist		
<b>Side Door</b>	36" Wide Flush Lock, Wire Holdback		
<b>Vents</b>	Sidewall Airflow		
<b>Fenders</b>	Smooth Aluminum		
<b>Axle</b>	(2) 3500 lb. Drop Spring Brake		
<b>Hubs</b>	Easy Lube		
<b>Breakaway</b>	Battery, Switch, and Lanyard		
<b>Tires</b>	ST205/75R15C 6-PR		
<b>Exterior Finish</b>	.030" Aluminum		
<b>Undercoating</b>	Automotive		
<b>Exterior Fastening</b>	Color Matching Screws		
<b>Exterior Trim</b>	1.5" Bottom Extrusion, 1.5" Top Extrusion, Color Matching Rear Hoop		
<b>Stone Guard</b>	16" ATP		
<b>Roof</b>	Flat Top Seamless Aluminum		
<b>Interior Walls</b>	Engineered Wood		
<b>Interior Trim</b>	Vinyl Wall Transitions		
<b>Ceiling</b>	Lauan Strip		
<b>Flooring</b>	3/4" Engineered Wood		
<b>Interior Lights</b>	(2) LED		
<b>Switches</b>	(1) Dome Light, 12V		
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings		
<b>Connector Plug</b>	Round 7-pin Blade		
<b>Exterior Lights</b>	Full LED, DOT Compliant		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
<b>Model #</b>	K10216STSVCH-100	K10218STSVCH-100	K10220STSVCH-100	K10222STSVCH-100	K10224STSVCH-100
<b>CAPACITIES</b>					
<b>GVWR (lbs)</b>	9900				
<b>GAWR (lbs/axle)</b>	5000				
<b>CHASSIS</b>					
<b>Tongue</b>	6" x 2" Steel Triple Tube				
<b>Crossmembers</b>	Formed Steel, 16" On-Center				
<b>Integrated Step(s)</b>	Interior Recessed				
<b>Coupler</b>	2-5/16" A-Frame				
<b>Safety Chains</b>	DOT Compliant				
<b>Tongue Jack</b>	2K Coupler Mounted				
<b>Wall Studs</b>	Steel Tube, 24" On-Center				
<b>Roof Bows</b>	Steel Tube, 24" On-Center				
<b>Front Profile</b>	V-Nose				
<b>Beavertail</b>	32"				48"
<b>Ramp(s)</b>	4000 lb. with Assist				
<b>Side Door</b>	36" Wide Flush Lock, Wire Holdback				
<b>Vents</b>	Sidewall Airflow				
<b>Fenders</b>	Smooth Aluminum				
<b>Axle</b>	(2) 5200 lb. Drop Spring Brake				
<b>Hubs</b>	Easy Lube				
<b>Breakaway</b>	Battery, Switch, and Lanyard				
<b>Tires</b>	ST225/75R15D 8-PR				
<b>Exterior Finish</b>	.030" Aluminum				
<b>Undercoating</b>	Automotive				
<b>Exterior Fastening</b>	Color Matching Screws				
<b>Exterior Trim</b>	1.5" Bottom Extrusion, 1.5" Top Extrusion, Color Matching Rear Hoop				
<b>Stone Guard</b>	16" ATP				
<b>Roof</b>	Flat Top Seamless Aluminum				
<b>Interior Walls</b>	Engineered Wood				
<b>Interior Trim</b>	Vinyl Wall Transitions				
<b>Ceiling</b>	Lauan Strip				
<b>Flooring</b>	3/4" Engineered Wood				
<b>Interior Lights</b>	(2) LED				
<b>Switches</b>	(1) Dome Light, 12V				
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings				
<b>Connector Plug</b>	Round 7-pin Blade				
<b>Exterior Lights</b>	Full LED, DOT Compliant				

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.