

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Model #</b>	K10216VSSVCH-140	K10218VSSVCH-140	K10220VSSVCH-140	K10222VSSVCH-140	K10224VSSVCH-140	K10226VSSVCH-140
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	14000					
<b>GAWR (lbs/axle)</b>	7000					
<b>CHASSIS</b>						
<b>Frame</b>	8" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 8" x 2" Steel Triple Tube					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>	Interior Recessed					
<b>Coupler</b>	2-5/16" Adjustable					
<b>Safety Chains</b>	DOT Compliant					
<b>Tongue Jack</b>	7K Drop Leg, Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	30" Aero Wedge					
<b>Beavertail</b>	32"			48"		
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, 4000 lb. with Assist					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Vents</b>	Sidewall Airflow					
<b>Fenders</b>	Smooth Aluminum					
<b>Axle</b>	(2) 7000 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST235/80R16E 10-PR					
<b>Wheels</b>	16", 8-Hole Aluminum					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" ATP					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Dome Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION CAR HAULER  
VISION FLAT TOP AERO WEDGE 14K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Connector Plug</b>	Round 7-pin Blade					
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>DIMENSIONS</b>						
<b>Overall Length</b>	257"	281"	305"	329"	353"	377"
<b>Deck Length</b>	215"	239"	263"	287"	311"	335"
<b>Deck Width</b>	96.88"					
<b>Deck Height</b>	25.25"					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 28	
<b>Model #</b>	K10228VSSVCH-140
<b>CAPACITIES</b>	
<b>GVWR (lbs)</b>	14000
<b>GAWR (lbs/axle)</b>	7000
<b>CHASSIS</b>	
<b>Frame</b>	8" x 2" Steel Tube
<b>Tongue</b>	6" Extension, 8" x 2" Steel Triple Tube
<b>Crossmembers</b>	Formed Steel, 16" On-Center
<b>Integrated Step(s)</b>	Interior Recessed
<b>Coupler</b>	2-5/16" Adjustable
<b>Safety Chains</b>	DOT Compliant
<b>Tongue Jack</b>	7K Drop Leg, Set-Back
<b>Wall Studs</b>	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
<b>Front Profile</b>	30" Aero Wedge
<b>Beavertail</b>	48"
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, 4000 lb. with Assist
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback
<b>Vents</b>	Sidewall Airflow
<b>Fenders</b>	Smooth Aluminum
<b>Axle</b>	(2) 7000 lb. Drop Spring Brake
<b>Hubs</b>	Easy Lube
<b>Breakaway</b>	Battery, Switch, and Lanyard
<b>Tires</b>	ST235/80R16E 10-PR
<b>Wheels</b>	16", 8-Hole Aluminum
<b>Exterior Finish</b>	.030" Aluminum
<b>Undercoating</b>	Automotive
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
<b>Exterior Trim</b>	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop
<b>Stone Guard</b>	24" ATP
<b>Roof</b>	Flat Top Seamless Aluminum
<b>Interior Walls</b>	Engineered Wood
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions
<b>Ceiling</b>	White ThermoPly®
<b>Flooring</b>	3/4" Engineered Wood
<b>Interior Lights</b>	(2) LED
<b>Switches</b>	(1) Dome Light, 12V
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings
<b>Connector Plug</b>	Round 7-pin Blade
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 28

**DIMENSIONS**

<b>Overall Length</b>	401"
<b>Deck Length</b>	359"
<b>Deck Width</b>	96.88"
<b>Deck Height</b>	25.25"

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Model #</b>	K10216VSSVCH-070	K10218VSSVCH-070	K10220VSSVCH-070	K10222VSSVCH-070	K10224VSSVCH-070	K10226VSSVCH-070
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	7000					
<b>GAWR (lbs/axle)</b>	3500					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 6" x 2" Steel Triple Tube					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>	Interior Recessed					
<b>Coupler</b>	2-5/16" Adjustable					
<b>Safety Chains</b>	DOT Compliant					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	30" Aero Wedge					
<b>Beavertail</b>	32"			48"		
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, 4000 lb. with Assist					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Vents</b>	Sidewall Airflow					
<b>Fenders</b>	Smooth Aluminum					
<b>Axle</b>	(2) 3500 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST205/75R15C 6-PR					
<b>Wheels</b>	15", 5-Hole Aluminum					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" ATP					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Dome Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION CAR HAULER  
VISION FLAT TOP AERO WEDGE 7K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Connector Plug</b>	Round 7-pin Blade					
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>DIMENSIONS</b>						
<b>Overall Length</b>	257"	281"	305"	329"	353"	377"
<b>Deck Length</b>	215"	239"	263"	287"	311"	335"
<b>Deck Width</b>	96.88"					
<b>Deck Height</b>	20.75"					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 28	
<b>Model #</b>	K10228VSSVCH-070
<b>CAPACITIES</b>	
<b>GVWR (lbs)</b>	7000
<b>GAWR (lbs/axle)</b>	3500
<b>CHASSIS</b>	
<b>Frame</b>	8" x 2" Steel Tube
<b>Tongue</b>	6" Extension, 8" x 2" Steel Triple Tube
<b>Crossmembers</b>	Formed Steel, 16" On-Center
<b>Integrated Step(s)</b>	Interior Recessed
<b>Coupler</b>	2-5/16" Adjustable
<b>Safety Chains</b>	DOT Compliant
<b>Tongue Jack</b>	5K Set-Back
<b>Wall Studs</b>	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
<b>Front Profile</b>	30" Aero Wedge
<b>Beavertail</b>	48"
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, 4000 lb. with Assist
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback
<b>Vents</b>	Sidewall Airflow
<b>Fenders</b>	Smooth Aluminum
<b>Axle</b>	(2) 3500 lb. Drop Spring Brake
<b>Hubs</b>	Easy Lube
<b>Breakaway</b>	Battery, Switch, and Lanyard
<b>Tires</b>	ST205/75R15C 6-PR
<b>Wheels</b>	15", 5-Hole Aluminum
<b>Exterior Finish</b>	.030" Aluminum
<b>Undercoating</b>	Automotive
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
<b>Exterior Trim</b>	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop
<b>Stone Guard</b>	24" ATP
<b>Roof</b>	Flat Top Seamless Aluminum
<b>Interior Walls</b>	Engineered Wood
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions
<b>Ceiling</b>	White ThermoPly®
<b>Flooring</b>	3/4" Engineered Wood
<b>Interior Lights</b>	(2) LED
<b>Switches</b>	(1) Dome Light, 12V
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings
<b>Connector Plug</b>	Round 7-pin Blade
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 28

## DIMENSIONS

<b>Overall Length</b>	401"
<b>Deck Length</b>	359"
<b>Deck Width</b>	96.88"
<b>Deck Height</b>	22.75"



	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Model #</b>	K10216VSSVCH-100	K10218VSSVCH-100	K10220VSSVCH-100	K10222VSSVCH-100	K10224VSSVCH-100	K10226VSSVCH-100
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	9900					
<b>GAWR (lbs/axle)</b>	5000					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 6" x 2" Steel Triple Tube					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>	Interior Recessed					
<b>Coupler</b>	2-5/16" Adjustable					
<b>Safety Chains</b>	DOT Compliant					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	30" Aero Wedge					
<b>Beavertail</b>	32"			48"		
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, 4000 lb. with Assist					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Vents</b>	Sidewall Airflow					
<b>Fenders</b>	Smooth Aluminum					
<b>Axle</b>	(2) 5200 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST225/75R15D 8-PR					
<b>Wheels</b>	15", 6-Hole Aluminum					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" ATP					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Dome Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**VISION CAR HAULER**  
**VISION FLAT TOP AERO WEDGE 10K**

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Connector Plug</b>	Round 7-pin Blade					
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>DIMENSIONS</b>						
<b>Overall Length</b>	257"	281"	305"	329"	353"	377"
<b>Deck Length</b>	215"	239"	263"	287"	311"	335"
<b>Deck Width</b>	96.88"					
<b>Deck Height</b>	21.75"					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 28	
<b>Model #</b>	K10228VSSVCH-100
<b>CAPACITIES</b>	
<b>GVWR (lbs)</b>	9900
<b>GAWR (lbs/axle)</b>	5000
<b>CHASSIS</b>	
<b>Frame</b>	8" x 2" Steel Tube
<b>Tongue</b>	6" Extension, 8" x 2" Steel Triple Tube
<b>Crossmembers</b>	Formed Steel, 16" On-Center
<b>Integrated Step(s)</b>	Interior Recessed
<b>Coupler</b>	2-5/16" Adjustable
<b>Safety Chains</b>	DOT Compliant
<b>Tongue Jack</b>	5K Set-Back
<b>Wall Studs</b>	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
<b>Front Profile</b>	30" Aero Wedge
<b>Beavertail</b>	48"
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, 4000 lb. with Assist
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback
<b>Vents</b>	Sidewall Airflow
<b>Fenders</b>	Smooth Aluminum
<b>Axle</b>	(2) 5200 lb. Drop Spring Brake
<b>Hubs</b>	Easy Lube
<b>Breakaway</b>	Battery, Switch, and Lanyard
<b>Tires</b>	ST225/75R15D 8-PR
<b>Wheels</b>	15", 6-Hole Aluminum
<b>Exterior Finish</b>	.030" Aluminum
<b>Undercoating</b>	Automotive
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
<b>Exterior Trim</b>	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop
<b>Stone Guard</b>	24" ATP
<b>Roof</b>	Flat Top Seamless Aluminum
<b>Interior Walls</b>	Engineered Wood
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions
<b>Ceiling</b>	White ThermoPly®
<b>Flooring</b>	3/4" Engineered Wood
<b>Interior Lights</b>	(2) LED
<b>Switches</b>	(1) Dome Light, 12V
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings
<b>Connector Plug</b>	Round 7-pin Blade
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 28

**DIMENSIONS**

<b>Overall Length</b>	401"
<b>Deck Length</b>	359"
<b>Deck Width</b>	96.88"
<b>Deck Height</b>	23.75"