

	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 16	8.5 x 18
Model #	K8414VSSV-140	K8416VSSV-140	K8418VSSV-140	K8420VSSV-140	K10216VSSV-140	K10218VSSV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
CHASSIS						
Frame	6" x 2" Steel Tube				8" x 2" Steel Tube	
Tongue	6" Extension, 6" x 2" Steel Triple Tube				6" Extension, 8" x 2" Steel Triple Tube	
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)					Interior Recessed	
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back				7K Drop Leg, Set-Back	
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	24" Aero Wedge				30" Aero Wedge	
Ramp(s)	12" Extension with Bullnose Cap, 2500 lb. with Assist				12" Extension with Bullnose Cap, 4000 lb. with Assist	
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders					Smooth Aluminum	
Axle	(2) 7000 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 16	8.5 x 18
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					
DIMENSIONS						
Overall Length					257"	281"
Deck Length					215"	239"
Deck Width					96.88"	
Deck Height					25.25"	

	8.5 x 20	8.5 x 22	8.5 x 24
Model #	K10220VSSV-140	K10222VSSV-140	K10224VSSV-140
CAPACITIES			
GVWR (lbs)		14000	
GAWR (lbs/axle)		7000	
CHASSIS			
Frame	8" x 2" Steel Tube		
Tongue	6" Extension, 8" x 2" Steel Triple Tube		
Crossmembers	Formed Steel, 16" On-Center		
Integrated Step(s)	Interior Recessed		
Coupler	2-5/16" Adjustable		
Safety Chains	DOT Compliant		
Tongue Jack	7K Drop Leg, Set-Back		
Wall Studs	Steel Tube, 16" On-Center		
Roof Bows	Steel Tube, 16" On-Center		
Front Profile	30" Aero Wedge		
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist		
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Sidewall Airflow		
Fenders	Smooth Aluminum		
Axle	(2) 7000 lb. Drop Spring Brake		
Hubs	Easy Lube		
Breakaway	Battery, Switch, and Lanyard		
Tires	ST235/80R16E 10-PR		
Wheels	16", 8-Hole Aluminum		
Exterior Finish	.030" Aluminum		
Undercoating	Automotive		
Exterior Fastening	VHB Bonded (Screwless)		
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop		
Stone Guard	24" ATP		
Roof	Flat Top Seamless Aluminum		
Interior Walls	Engineered Wood		
Interior Trim	Extruded Aluminum Wall Transitions		
Ceiling	White ThermoPly®		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) LED		
Switches	(1) Dome Light, 12V		
Connector Plug	Round 7-pin Blade		
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights		
DIMENSIONS			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 20	8.5 x 22	8.5 x 24
Overall Length	305"	329"	353"
Deck Length	263"	287"	311"
Deck Width		96.88"	
Deck Height		25.25"	

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
Model #	K10220VSSV-160	K10222VSSV-160	K10224VSSV-160	K10226VSSV-160	K10228VSSV-160	K10230VSSV-160
CAPACITIES						
GVWR (lbs)	16000					
GAWR (lbs/axle)	8000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	6" Extension, 8" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	12K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	30" Aero Wedge					
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Smooth Aluminum					
Axle	(2) 8000 lb. Drop Spring Brake					
Hubs	Oil Bath					
Breakaway	Battery, Switch, and Lanyard					
Tires	215/75R17.5J 18-PR					
Wheels	17.5", 8-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	5 x 8	5 x 8	5 x 10	5 x 10	6 x 10	6 x 10
Model #	K6008VSSV-035	K6008VSSV-030	K6010VSSV-030	K6010VSSV-035	K7210VSSV-030	K7210VSSV-035
CAPACITIES						
GVWR (lbs)	3500	2990		3500	2990	3500
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	3" x 2" Aluminum Tube					
Tongue	3" x 2" Steel Tube, 6" Extension					
Crossmembers	Formed Steel, 16" On-Center					
Coupler	2" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	24" Aero Wedge					
Ramp(s)	12" Extension with Bullnose Cap, 1500 lb. with Assist					
Side Door					32" Wide Flush Lock, Cast Aluminum Holdback	
Vents	Sidewall Airflow					
Axle	3500 lb. Drop Spring Brake	3500 lb. Drop Spring Idler		3500 lb. Drop Spring Brake	3500 lb. Drop Spring Idler	3500 lb. Drop Spring Brake
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard			Battery, Switch, and Lanyard		Battery, Switch, and Lanyard
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade	Flat 4-pin		Round 7-pin Blade	Flat 4-pin	Round 7-pin Blade

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	5 x 8	5 x 8	5 x 10	5 x 10	6 x 10	6 x 10
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights	Full LED, DOT Compliant	Full LED, DOT Compliant, Integrated Backup/Taillights	Full LED, DOT Compliant, Integrated Backup/Taillights	Full LED, DOT Compliant	Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	6 x 12		6 x 14		7 x 12		
Model #	K7212VSSV-035	K7212VSSV-030	K7214VSSV-035	K7214VSSV-030	K8412VSSV-035		
CAPACITIES							
GVWR (lbs)	2990		3500		3500		
GAWR (lbs/axle)	3500						
CHASSIS							
Frame						4" x 2" Steel Tube	
Tongue	3" x 2" Steel Tube, 6" Extension					6" Extension, 6" x 2" Steel Tube	
Crossmembers	Formed Steel, 16" On-Center						
Coupler	2" Adjustable						
Safety Chains	DOT Compliant						
Tongue Jack	2K Set-Back						
Wall Studs	Steel Tube, 16" On-Center						
Roof Bows	Steel Tube, 16" On-Center						
Front Profile	24" Aero Wedge						
Ramp(s)	12" Extension with Bullnose Cap, 1500 lb. with Assist					12" Extension with Bullnose Cap, 2500 lb. with Assist	
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback						
Vents	Sidewall Airflow						
Axle	3500 lb. Drop Spring Brake	3500 lb. Drop Spring Idler	3500 lb. Drop Spring Brake	3500 lb. Drop Spring Idler	3500 lb. Drop Spring Brake		
Hubs	Easy Lube						
Breakaway	Battery, Switch, and Lanyard		Battery, Switch, and Lanyard		Battery, Switch, and Lanyard		
Tires	ST205/75R15C 6-PR						
Wheels	15", 5-Hole Aluminum						
Exterior Finish	.030" Aluminum						
Undercoating	Automotive						
Exterior Fastening	VHB Bonded (Screwless)						
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop						
Stone Guard	24" ATP						
Roof	Flat Top Seamless Aluminum						
Interior Walls	Engineered Wood						
Interior Trim	Extruded Aluminum Wall Transitions						
Ceiling	White ThermoPly®						
Flooring	3/4" Engineered Wood						
Interior Lights	(2) LED						
Switches	(1) Dome Light, 12V						

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	6 x 12	6 x 12	6 x 14	6 x 14	7 x 12
Connector Plug	Round 7-pin Blade	Flat 4-pin	Round 7-pin Blade	Flat 4-pin	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights	Full LED, DOT Compliant	Full LED, DOT Compliant, Integrated Backup/Taillights	Full LED, DOT Compliant	Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20
Model #	K7212VSSV-070	K8412VSSV-070	K8414VSSV-070	K8416VSSV-070	K8418VSSV-070	K8420VSSV-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	24" Aero Wedge					
Ramp(s)	12" Extension with Bullnose Cap, 1500 lb. with Assist	12" Extension with Bullnose Cap, 2500 lb. with Assist				
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 12	8.5 x 14
Model #	K9014VSSV-070	K9016VSSV-070	K9018VSSV-070	K9020VSSV-070	K10212VSSV-070	K10214VSSV-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	24" Aero Wedge				30" Aero Wedge	
Ramp(s)	12" Extension with Bullnose Cap, 2500 lb. with Assist				12" Extension with Bullnose Cap, 4000 lb. with Assist	
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Smooth Aluminum					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 12	8.5 x 14
DIMENSIONS						
Overall Length					209"	233"
Deck Length					167"	191"
Deck Width					96.88"	
Deck Height					20.75"	

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	K10216VSSV-070	K10218VSSV-070	K10220VSSV-070	K10222VSSV-070	K10224VSSV-070	K10226VSSV-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	30" Aero Wedge					
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Smooth Aluminum					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					
DIMENSIONS						

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Overall Length	257"	281"	305"	329"	353"	377"
Deck Length	215"	239"	263"	287"	311"	335"
Deck Width	96.88"					
Deck Height	20.75"					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 28	
Model #	K10228VSSV-070
CAPACITIES	
GVWR (lbs)	7000
GAWR (lbs/axle)	3500
CHASSIS	
Frame	6" x 2" Steel Tube
Tongue	6" Extension, 8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Adjustable
Safety Chains	DOT Compliant
Tongue Jack	5K Set-Back
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	30" Aero Wedge
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow
Fenders	Smooth Aluminum
Axle	(2) 3500 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST205/75R15C 6-PR
Wheels	15", 5-Hole Aluminum
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop
Stone Guard	24" ATP
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White ThermoPly®
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights
DIMENSIONS	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 28	
Overall Length	401"
Deck Length	359"
Deck Width	96.88"
Deck Height	22.75"

	6 x 10	6 x 12	6 x 14
Model #	K7210VSSV-050	K7212VSSV-050	K7214VSSV-050
CAPACITIES			
GVWR (lbs)		5000	
GAWR (lbs/axle)		5000	
CHASSIS			
Tongue	3" x 2" Steel Tube, 6" Extension		
Crossmembers	Formed Steel, 16" On-Center		
Coupler	2" Adjustable		
Safety Chains	DOT Compliant		
Tongue Jack	2K Set-Back		
Wall Studs	Steel Tube, 16" On-Center		
Roof Bows	Steel Tube, 16" On-Center		
Front Profile	24" Aero Wedge		
Ramp(s)	12" Extension with Bullnose Cap, 1500 lb. with Assist		
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Sidewall Airflow		
Axle	5200 lb. Drop Spring Brake		
Hubs	Easy Lube		
Breakaway	Battery, Switch, and Lanyard		
Tires	ST225/75R15D 8-PR		
Wheels	15", 6-Hole Aluminum		
Exterior Finish	.030" Aluminum		
Undercoating	Automotive		
Exterior Fastening	VHB Bonded (Screwless)		
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop		
Stone Guard	24" ATP		
Roof	Flat Top Seamless Aluminum		
Interior Walls	Engineered Wood		
Interior Trim	Extruded Aluminum Wall Transitions		
Ceiling	White ThermoPly®		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) LED		
Switches	(1) Dome Light, 12V		
Connector Plug	Round 7-pin Blade		
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	7 x 14	7 x 16	7 x 18	7 x 20	7 x 22	7.5 x 14
Model #	K8414VSSV-100	K8416VSSV-100	K8418VSSV-100	K8420VSSV-100	K8422VSSV-100	K9014VSSV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	24" Aero Wedge					
Ramp(s)	12" Extension with Bullnose Cap, 2500 lb. with Assist					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 12	8.5 x 14	8.5 x 16
Model #	K9016VSSV-100	K9018VSSV-100	K9020VSSV-100	K10212VSSV-100	K10214VSSV-100	K10216VSSV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	24" Aero Wedge			30" Aero Wedge		
Ramp(s)	12" Extension with Bullnose Cap, 2500 lb. with Assist			12" Extension with Bullnose Cap, 4000 lb. with Assist		
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback			36" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Sidewall Airflow					
Fenders	Smooth Aluminum					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					
DIMENSIONS						

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION CARGO
VISION FLAT TOP AERO WEDGE 10K

	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 12	8.5 x 14	8.5 x 16
Overall Length				209"	233"	257"
Deck Length				167"	191"	215"
Deck Width				96.88"		
Deck Height				21.75"		



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28
Model #	K10218VSSV-100	K10220VSSV-100	K10222VSSV-100	K10224VSSV-100	K10226VSSV-100	K10228VSSV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					6" Extension, 8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back					5K Set-Back
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	30" Aero Wedge					
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Smooth Aluminum					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION CARGO VISION FLAT TOP AERO WEDGE 10K

	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28
DIMENSIONS						
Overall Length	281"	305"	329"	353"	377"	401"
Deck Length	239"	263"	287"	311"	335"	359"
Deck Width	96.88"					
Deck Height	21.75"					23.75"



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10230VSSV-100	K10232VSSV-100	K10234VSSV-100
CAPACITIES			
GVWR (lbs)	9900		
GAWR (lbs/axle)	5000		
CHASSIS			
Frame	6" x 2" Steel Tube		
Tongue	6" Extension, 8" x 2" Steel Triple Tube		
Crossmembers	Formed Steel, 16" On-Center		
Integrated Step(s)	Interior Recessed		
Coupler	2-5/16" Adjustable		
Safety Chains	DOT Compliant		
Tongue Jack	5K Set-Back		
Wall Studs	Steel Tube, 16" On-Center		
Roof Bows	Steel Tube, 16" On-Center		
Front Profile	30" Aero Wedge		
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist		
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Sidewall Airflow		
Fenders	Smooth Aluminum		
Axle	(2) 5200 lb. Drop Spring Brake		
Hubs	Easy Lube		
Breakaway	Battery, Switch, and Lanyard		
Tires	ST225/75R15D 8-PR		
Wheels	15", 6-Hole Aluminum		
Exterior Finish	.030" Aluminum		
Undercoating	Automotive		
Exterior Fastening	VHB Bonded (Screwless)		
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop		
Stone Guard	24" ATP		
Roof	Flat Top Seamless Aluminum		
Interior Walls	Engineered Wood		
Interior Trim	Extruded Aluminum Wall Transitions		
Ceiling	White ThermoPly®		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) LED		
Switches	(1) Dome Light, 12V		
Connector Plug	Round 7-pin Blade		
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights		
DIMENSIONS			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 30	8.5 x 32	8.5 x 34
Overall Length	425"	449"	473"
Deck Length	383"	407"	431"
Deck Width	96.88"		
Deck Height	23.75"		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.