

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
	K10220VSSVCHA-	K10222VSSVCHA-	K10224VSSVCHA-	K10226VSSVCHA-	K10228VSSVCHA-	K10230VSSVCHA-
Model #	100	100	100	100	100	100
CAPACITIES						
GVWR (lbs)			99	00		
GAWR (lbs/axle)			50	00		
CHASSIS						
Frame		6" x 2" Double Holl	ow Aluminum Tube		8" x 2" Double Holl	low Aluminum Tube
_					8" x 2" Double Holl	ow Aluminum Triple
Tongue	C	o" x 2" Double Hollow	Aluminum Triple Tub	e	Tu	ıbe
Crossmembers			Aluminum Tube	e, 16" On-Center		
Coupler			2-5/16"	A-Frame		
Safety Chains				mpliant		
Tongue Jack		2K Couple	er Mounted		5K Couple	er Mounted
Wall Studs				e, 16" On-Center		
Roof Bows				e, 16" On-Center		
Front Profile			•	ose with 6" Drop		
Beavertail				8"		
Ramp(s)			•	minum with Assist	_	
Side Door		36	" Wide Flush Lock, C		ack	
Vents				l Airflow		
Fenders				Treadplate		
Axle			• •	op Spring Brake		
Hubs			•	Lube		
Breakaway Tires			•	h, and Lanyard R15D 8-PR		
Wheels				ole Steel		
Exterior Finish			•	uminum		
Exterior Fastening				(Screwless)		
Exterior Trim	,	1.5" Bottom Extrusion	n, 2.5" Top Extrusion,	,	r Matching Rear Hoo	D .
Stone Guard			· ·	oed ATP		
Roof				less Aluminum		
Interior Walls			•	ed Wood		
Interior Trim			Vinyl Wall	Transitions		
Ceiling			Lauar	n Strip		
Flooring			3/4" Engine	eered Wood		
Interior Lights			(2)	LED		
Switches			(1) Dome	Light, 12V		
Cargo Control			(4) 5000 lb. Re	cessed D-Rings		
<b>Connector Plug</b>			Round 7-	pin Blade		





# VISION ALUMINUM CAR HAULER VISION FLAT TOP V-NOSE 10K

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
<b>Exterior Lights</b>		Full LE	D, DOT Compliant, In	tegrated Backup/Tai	llights	





	8.5 x 32
Model #	K10232VSSVCHA-100
CAPACITIES	11.102.02.700.701.11.100
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Frame	8" x 2" Double Hollow Aluminum Tube
Tongue	8" x 2" Double Hollow Aluminum Triple Tube
Crossmembers	Aluminum Tube, 16" On-Center
Coupler	2-5/16" A-Frame
<b>Safety Chains</b>	DOT Compliant
Tongue Jack	5K Coupler Mounted
Wall Studs	Aluminum Tube, 16" On-Center
Roof Bows	Aluminum Tube, 16" On-Center
Front Profile	30" Sloped V-Nose with 6" Drop
Beavertail	48"
Ramp(s)	12" Extension, Aluminum with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 5200 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST225/75R15D 8-PR
Wheels	15", 6-Hole Steel
Exterior Finish	.030" Aluminum
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
Exterior Trim	1.5" Bottom Extrusion, 2.5" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop
Stone Guard	24" Sloped ATP
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Vinyl Wall Transitions
Ceiling	Lauan Strip
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights





	7.5 x 12	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 16				
Model #	K9012VSSVA- 100	K9014VSSVA- 100	K9016VSSVA- 100	K9018VSSVA- 100	K9020VSSVA- 100	K10216VSSVA-100				
CAPACITIES										
GVWR (lbs)				9900						
GAWR (lbs/axle)				5000						
CHASSIS										
Frame		4'	x 2" Aluminum Tu	be		6" x 2" Double Hollow Aluminum Tube				
Tongue		5'	x 2" Aluminum Tu	be		6" x 2" Double Hollow Aluminum Triple Tube				
Crossmembers			Alumir	ium Tube, 24" On-0	Center					
Coupler				2-5/16" A-Frame						
Safety Chains				DOT Compliant						
Tongue Jack				K Coupler Mounte						
Wall Studs				num Tube, 16" On-0						
Roof Bows				num Tube, 24" On-0	Center					
Front Profile		24" Slo	ped V-Nose with 1	•		30" Sloped V-Nose with 12" Drop				
Ramp(s)			12" Exten	sion, Aluminum wi	ith Assist					
Side Door		32" Wide Flus	h Lock, Cast Alum	inum Holdback		36" Wide Flush Lock, Cast Aluminum Holdback				
Vents				Sidewall Airflow						
Fenders			Al	uminum Treadplat	te					
Axle			(2) 520	00 lb. Drop Spring	Brake					
Hubs				Easy Lube						
Breakaway			Batte	ry, Switch, and Lar	nyard					
Tires			S	T225/75R15D 8-PI	R					
Wheels				15", 6-Hole Steel						
Exterior Finish				.030" Aluminum						
<b>Exterior Fastening</b>				B Bonded (Screwle						
Exterior Trim		2.7" Bottom Ext	· · · · · · · · · · · · · · · · · · ·	xtrusion, ATP Nose	• •	hing Rear Hoop				
Roof				op Seamless Alum	inum					
Interior Walls				Engineered Wood	•-•					
Interior Trim			Extruded	Aluminum Wall Tra	ansitions					
Ceiling				Lauan Strip						
Flooring			3/-	4" Engineered Woo	od					
Interior Lights				(2) LED	_					
Switches			· '	1) Dome Light, 12\						
Connector Plug				Round 7-pin Blade						
Exterior Lights			Full LED, DOT Com	pliant, Integrated	Backup/Taillights					







	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24					
Model #	K10218VSSVA-100	K10220VSSVA-100	K10222VSSVA-100	K10224VSSVA-100					
CAPACITIES									
GVWR (lbs)	9900								
GAWR (lbs/axle)	5000								
CHASSIS									
Frame	6" x 2" Double Hollow Aluminum Tube								
Tongue		6" x 2" Double Hollow	Aluminum Triple Tube						
Crossmembers		Aluminum Tube	, 24" On-Center						
Coupler		2-5/16"	A-Frame						
Safety Chains		DOT Co	mpliant						
Tongue Jack		2K Couple	r Mounted						
Wall Studs		Aluminum Tube	, 16" On-Center						
Roof Bows		Aluminum Tube	, 24" On-Center						
Front Profile		30" Sloped V-No	se with 12" Drop						
Ramp(s)		12" Extension, Alu	minum with Assist						
Side Door		36" Wide Flush Lock, Ca	ast Aluminum Holdback						
/ents		Sidewal	l Airflow						
enders		Aluminum	Treadplate						
\xle		(2) 5200 lb. Dro	op Spring Brake						
lubs		Easy	Lube						
Breakaway		Battery, Switcl	h, and Lanyard						
ires		ST225/75	R15D 8-PR						
Vheels		15", 6-H	ole Steel						
Exterior Finish		.030" Al	uminum						
Exterior Fastening		VHB Bonded	(Screwless)						
Exterior Trim	2.7" Botton	n Extrusion, 2.7" Top Extrusion,	ATP Nose Cap, Color Matching	Rear Hoop					
Roof		Flat Top Seam	less Aluminum						
nterior Walls		Engineer	ed Wood						
nterior Trim		Extruded Aluminu	m Wall Transitions						
Ceiling		Lauar	Strip						
looring		3/4" Engine	eered Wood						
nterior Lights		(2)	LED						
Switches		(1) Dome	Light, 12V						
Connector Plug		Round 7-	pin Blade						
Exterior Lights		Full LED, DOT Compliant, Ir	tegrated Backup/Taillights						



2025 Pricing





	6 x 10	6 x 12	6 x 14				
Model #	K7210VSSVA-030	K7212VSSVA-030	K7214VSSVA-030				
CAPACITIES							
GVWR (lbs)		2990					
GAWR (lbs/axle)	3500						
CHASSIS							
Frame		3" x 2" Aluminum Tube					
Tongue		4" x 2" Aluminum Tube					
Crossmembers		Aluminum Tube, 24" On-Center					
Coupler		2" A-Frame					
Safety Chains		DOT Compliant					
Tongue Jack		2K Coupler Mounted					
Wall Studs		Aluminum Tube, 16" On-Center					
Roof Bows		Aluminum Tube, 24" On-Center					
Front Profile		24" Sloped V-Nose with 12" Drop					
Ramp(s)		12" Extension, Aluminum with Assist					
Side Door	32	2" Wide Flush Lock, Cast Aluminum Holdba	ck				
Vents		Sidewall Airflow					
Fenders		Aluminum Treadplate					
Axle		3500 lb. Drop Spring Idler					
Hubs		Easy Lube					
Tires		ST205/75R15C 6-PR					
Wheels		15", 5-Hole Steel					
Exterior Finish		.030" Aluminum					
Exterior Fastening		VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusio	n, 2.7" Top Extrusion, ATP Nose Cap, Color	Matching Rear Hoop				
Roof		Flat Top Seamless Aluminum					
Interior Walls		Engineered Wood					
Interior Trim		Extruded Aluminum Wall Transitions					
Ceiling		Lauan Strip					
Flooring		3/4" Engineered Wood					
Interior Lights		(2) LED					
Switches		(1) Dome Light, 12V					
Connector Plug		Flat 4-pin					
Exterior Lights		Full LED, DOT Compliant					







	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	7.5 x 12			
Model #	K7212VSSVA-070	K8412VSSVA-070	K8414VSSVA-070	K8416VSSVA-070	K8418VSSVA-070	K9012VSSVA-070			
CAPACITIES									
GVWR (lbs)	7000								
GAWR (lbs/axle)			3500						
CHASSIS									
Frame			4" x 2" Alumir	num Tube					
Tongue	4" x 2" Aluminum Tube		5	" x 2" Aluminum Tub	e				
Crossmembers			Aluminum Tube, 2	24" On-Center					
Coupler			2-5/16" A-	Frame					
Safety Chains			DOT Com	pliant					
Tongue Jack			2K Coupler N	Mounted					
Wall Studs			Aluminum Tube, 1	6" On-Center					
<b>Roof Bows</b>			Aluminum Tube, 2	24" On-Center					
Front Profile			24" Sloped V-Nose	with 12" Drop					
Ramp(s)			12" Extension, Alumi	num with Assist					
Side Door		32" W	lide Flush Lock, Cast		k				
Vents			Sidewall A	irflow					
Fenders			Aluminum Tr	eadplate					
Axle			(2) 3500 lb. Drop						
Hubs			Easy Lu						
Breakaway			Battery, Switch,	•					
Tires			ST205/75R1						
Wheels			15", 5-Hole						
Exterior Finish			.030" Alun						
Exterior Fastening			VHB Bonded (S	· · · · · · · · · · · · · · · · · · ·					
Exterior Trim	2.7"	Bottom Extrusion, 2	2.7" Top Extrusion, A	•	Matching Rear Hoop				
Roof			Flat Top Seamles						
Interior Walls			Engineered						
Interior Trim			Extruded Aluminum						
Ceiling			Lauan S	-					
Flooring			3/4" Engineer						
Interior Lights			(2) LE						
Switches			(1) Dome Lig						
Connector Plug		FU.1 FB	Round 7-pi		-h-				
Exterior Lights		Full LED,	DOT Compliant, Inte	grated Backup/Tailli	gnts				







	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 16	8.5 x 18			
Model #	K9014VSSVA-	K9016VSSVA-	K9018VSSVA-	K9020VSSVA-	K10216VSSVA-070	K10218VSSVA-07			
Model #	070	070	070	070	K10210V33VA-070	K10210V33VA-07			
CAPACITIES									
GVWR (lbs)				7000					
GAWR (lbs/axle)		3500							
CHASSIS									
Frame		4" x 2" Aluı	minum Tube		6" x 2" Double Holl	low Aluminum Tube			
Tongue		5" x 2" Aluı	minum Tube		6" x 2" Double Hollow	Aluminum Triple Tul			
Crossmembers			Aluminum	Tube, 24" On-Cente	r				
Coupler			2-5	/16" A-Frame					
Safety Chains			DO	T Compliant					
Tongue Jack			2K Co	oupler Mounted					
Wall Studs			Aluminum	Tube, 16" On-Cente	r				
Roof Bows			Aluminum	Tube, 24" On-Cente	r				
Front Profile		24" Sloped V-No	ose with 12" Drop		30" Sloped V-No	ose with 12" Drop			
Ramp(s)			12" Extension	ı, Aluminum with As	sist				
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback  36" Wide Flush Lock, Cast Alumi					·			
Vents			Sid	ewall Airflow					
Fenders			Alumi	num Treadplate					
Axle			(2) 3500 lb	o. Drop Spring Brake					
Hubs				Easy Lube					
Breakaway			Battery, S	witch, and Lanyard					
Tires			ST20	5/75R15C 6-PR					
Wheels			15"	, 5-Hole Steel					
Exterior Finish			.03	0" Aluminum					
Exterior Fastening			VHB Bo	nded (Screwless)					
Exterior Trim		2.7" Bottom Extru	· ·		, Color Matching Rear H	оор			
Roof			•	Seamless Aluminum					
Interior Walls			<u>-</u>	ineered Wood					
Interior Trim				minum Wall Transiti	ons				
Ceiling 				auan Strip					
Flooring			3/4" E	ngineered Wood					
Interior Lights				(2) LED					
Switches			, ,	ome Light, 12V					
Connector Plug				nd 7-pin Blade					
Exterior Lights		Ful	II LED, DOT Complia	nt, Integrated Backı	up/Taillights				







	8.5 x 20	8.5 x 22	8.5 x 24					
Model #	K10220VSSVA-070	K10222VSSVA-070	K10224VSSVA-070					
CAPACITIES								
GVWR (lbs)		7000						
GAWR (lbs/axle)	3500							
CHASSIS								
Frame		6" x 2" Double Hollow Aluminum Tube						
Tongue	6"	x 2" Double Hollow Aluminum Triple Tube	2					
Crossmembers		Aluminum Tube, 24" On-Center						
Coupler		2-5/16" A-Frame						
Safety Chains		DOT Compliant						
Tongue Jack		2K Coupler Mounted						
Wall Studs		Aluminum Tube, 16" On-Center						
Roof Bows		Aluminum Tube, 24" On-Center						
Front Profile		30" Sloped V-Nose with 12" Drop						
Ramp(s)		12" Extension, Aluminum with Assist						
Side Door	36"	Wide Flush Lock, Cast Aluminum Holdbac	ck					
Vents		Sidewall Airflow						
Fenders		Aluminum Treadplate						
Axle		(2) 3500 lb. Drop Spring Brake						
Hubs		Easy Lube						
Breakaway		Battery, Switch, and Lanyard						
Tires		ST205/75R15C 6-PR						
Wheels		15", 5-Hole Steel						
Exterior Finish		.030" Aluminum						
Exterior Fastening		VHB Bonded (Screwless)						
Exterior Trim	2.7" Bottom Extrusion,	2.7" Top Extrusion, ATP Nose Cap, Color	Matching Rear Hoop					
Roof		Flat Top Seamless Aluminum						
Interior Walls		Engineered Wood						
Interior Trim		Extruded Aluminum Wall Transitions						
Ceiling		Lauan Strip						
Flooring		3/4" Engineered Wood						
Interior Lights		(2) LED						
Switches		(1) Dome Light, 12V						
Connector Plug		Round 7-pin Blade						
Exterior Lights	Full LEI	D, DOT Compliant, Integrated Backup/Taill	lights					







	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24					
Model #	K10216VSSVCHA-070	K10218VSSVCHA-070	K10220VSSVCHA-070	K10222VSSVCHA-070	K10224VSSVCHA-070					
CAPACITIES										
GVWR (lbs)			7000							
GAWR (lbs/axle)			3500							
CHASSIS										
Frame		6" x 2'	" Double Hollow Aluminun	n Tube						
Tongue		6" x 2" Do	ouble Hollow Aluminum Ti	riple Tube						
Crossmembers			uminum Tube, 16" On-Cen	•						
Coupler			2-5/16" A-Frame							
Safety Chains			DOT Compliant							
Tongue Jack			2K Coupler Mounted							
Wall Studs		Alı	uminum Tube, 16" On-Cen	ter						
Roof Bows		Alı	uminum Tube, 16" On-Cen	ter						
Front Profile		30	" Sloped V-Nose with 6" D	rop						
Beavertail				48"						
Ramp(s)		12" E	xtension, Aluminum with	Assist						
Side Door		36" Wide F	lush Lock, Cast Aluminun	n Holdback						
Vents			Sidewall Airflow							
Fenders			Aluminum Treadplate	_						
Axle		(2	) 3500 lb. Drop Spring Bra	ıke						
Hubs			Easy Lube							
Breakaway 		В	attery, Switch, and Lanya	rd						
Tires			ST205/75R15C 6-PR							
Wheels Exterior Finish			15", 5-Hole Steel							
			VHB Bonded (Screwless)							
Exterior Fastening Exterior Trim	1 5"	Rottom Extrusion 2 5" To	op Extrusion, ATP Nose C		Hoon					
Stone Guard	1.5	Dottom Extrusion, 2.5 To	24" Sloped ATP	ap, color matering Real	Ποορ					
Roof		F	at Top Seamless Aluminu	ım						
Interior Walls		•	Engineered Wood							
Interior Trim			Vinyl Wall Transitions							
Ceiling			Lauan Strip							
Flooring			3/4" Engineered Wood							
Interior Lights			(2) LED							
Switches			(1) Dome Light, 12V							
Cargo Control		(4	) 5000 lb. Recessed D-Rin	igs						
Connector Plug			Round 7-pin Blade							
<b>Exterior Lights</b>		Full LED, DOT	Compliant, Integrated Bad	ckup/Taillights						

