

	6 x 10	6 x 12	6 x 14
Model #	K7210VSSVA-030	K7212VSSVA-030	K7214VSSVA-030
CAPACITIES			
GVWR (lbs)		2990	
GAWR (lbs/axle)		3500	
CHASSIS			
Frame	3" x 2" Aluminum Tube		
Tongue	4" x 2" Aluminum Tube		
Crossmembers	Aluminum Tube, 24" On-Center		
Coupler	2" A-Frame		
Safety Chains	DOT Compliant		
Tongue Jack	2K Coupler Mounted		
Wall Studs	Aluminum Tube, 16" On-Center		
Roof Bows	Aluminum Tube, 24" On-Center		
Front Profile	24" Sloped V-Nose with 12" Drop		
Ramp(s)	12" Extension, Aluminum with Assist		
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Sidewall Airflow		
Fenders	Aluminum Treadplate		
Axle	3500 lb. Drop Spring Idler		
Hubs	Easy Lube		
Tires	ST205/75R15C 6-PR		
Wheels	15", 5-Hole Steel		
Exterior Finish	.030" Aluminum		
Exterior Fastening	VHB Bonded (Screwless)		
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop		
Roof	Flat Top Seamless Aluminum		
Interior Walls	Engineered Wood		
Interior Trim	Extruded Aluminum Wall Transitions		
Ceiling	Luan Strip		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) LED		
Switches	(1) Dome Light, 12V		
Connector Plug	Flat 4-pin		
Exterior Lights	Full LED, DOT Compliant		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	7.5 x 12
Model #	K7212VSSVA-070	K8412VSSVA-070	K8414VSSVA-070	K8416VSSVA-070	K8418VSSVA-070	K9012VSSVA-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	4" x 2" Aluminum Tube					
Tongue	4" x 2" Aluminum Tube		5" x 2" Aluminum Tube			
Crossmembers	Aluminum Tube, 24" On-Center					
Coupler	2-5/16" A-Frame					
Safety Chains	DOT Compliant					
Tongue Jack	2K Coupler Mounted					
Wall Studs	Aluminum Tube, 16" On-Center					
Roof Bows	Aluminum Tube, 24" On-Center					
Front Profile	24" Sloped V-Nose with 12" Drop					
Ramp(s)	12" Extension, Aluminum with Assist					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Steel					
Exterior Finish	.030" Aluminum					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Lauan Strip					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 16	8.5 x 18
Model #	K9014VSSVA-070	K9016VSSVA-070	K9018VSSVA-070	K9020VSSVA-070	K10216VSSVA-070	K10218VSSVA-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	4" x 2" Aluminum Tube				6" x 2" Double Hollow Aluminum Tube	
Tongue	5" x 2" Aluminum Tube				6" x 2" Double Hollow Aluminum Triple Tube	
Crossmembers	Aluminum Tube, 24" On-Center					
Coupler	2-5/16" A-Frame					
Safety Chains	DOT Compliant					
Tongue Jack	2K Coupler Mounted					
Wall Studs	Aluminum Tube, 16" On-Center					
Roof Bows	Aluminum Tube, 24" On-Center					
Front Profile	24" Sloped V-Nose with 12" Drop				30" Sloped V-Nose with 12" Drop	
Ramp(s)	12" Extension, Aluminum with Assist					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback				36" Wide Flush Lock, Cast Aluminum Holdback	
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Steel					
Exterior Finish	.030" Aluminum					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Lauan Strip					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 20	8.5 x 22	8.5 x 24
Model #	K10220VSSVA-070	K10222VSSVA-070	K10224VSSVA-070
CAPACITIES			
GVWR (lbs)		7000	
GAWR (lbs/axle)		3500	
CHASSIS			
Frame	6" x 2" Double Hollow Aluminum Tube		
Tongue	6" x 2" Double Hollow Aluminum Triple Tube		
Crossmembers	Aluminum Tube, 24" On-Center		
Coupler	2-5/16" A-Frame		
Safety Chains	DOT Compliant		
Tongue Jack	2K Coupler Mounted		
Wall Studs	Aluminum Tube, 16" On-Center		
Roof Bows	Aluminum Tube, 24" On-Center		
Front Profile	30" Sloped V-Nose with 12" Drop		
Ramp(s)	12" Extension, Aluminum with Assist		
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Sidewall Airflow		
Fenders	Aluminum Treadplate		
Axle	(2) 3500 lb. Drop Spring Brake		
Hubs	Easy Lube		
Breakaway	Battery, Switch, and Lanyard		
Tires	ST205/75R15C 6-PR		
Wheels	15", 5-Hole Steel		
Exterior Finish	.030" Aluminum		
Exterior Fastening	VHB Bonded (Screwless)		
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop		
Roof	Flat Top Seamless Aluminum		
Interior Walls	Engineered Wood		
Interior Trim	Extruded Aluminum Wall Transitions		
Ceiling	Lauan Strip		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) LED		
Switches	(1) Dome Light, 12V		
Connector Plug	Round 7-pin Blade		
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	7.5 x 12	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 16
Model #	K9012VSSVA-100	K9014VSSVA-100	K9016VSSVA-100	K9018VSSVA-100	K9020VSSVA-100	K10216VSSVA-100
CAPACITIES						
GVWR (lbs)	10000					9900
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	4" x 2" Aluminum Tube					6" x 2" Double Hollow Aluminum Tube
Tongue	5" x 2" Aluminum Tube					6" x 2" Double Hollow Aluminum Triple Tube
Crossmembers	Aluminum Tube, 24" On-Center					
Coupler	2-5/16" A-Frame					
Safety Chains	DOT Compliant					
Tongue Jack	2K Coupler Mounted					
Wall Studs	Aluminum Tube, 16" On-Center					
Roof Bows	Aluminum Tube, 24" On-Center					
Front Profile	24" Sloped V-Nose with 12" Drop					30" Sloped V-Nose with 12" Drop
Ramp(s)	12" Extension, Aluminum with Assist					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					36" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Steel					
Exterior Finish	.030" Aluminum					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Lauan Strip					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
Model #	K10218VSSVA-100	K10220VSSVA-100	K10222VSSVA-100	K10224VSSVA-100
CAPACITIES				
GVWR (lbs)	9900			
GAWR (lbs/axle)	5000			
CHASSIS				
Frame	6" x 2" Double Hollow Aluminum Tube			
Tongue	6" x 2" Double Hollow Aluminum Triple Tube			
Crossmembers	Aluminum Tube, 24" On-Center			
Coupler	2-5/16" A-Frame			
Safety Chains	DOT Compliant			
Tongue Jack	2K Coupler Mounted			
Wall Studs	Aluminum Tube, 16" On-Center			
Roof Bows	Aluminum Tube, 24" On-Center			
Front Profile	30" Sloped V-Nose with 12" Drop			
Ramp(s)	12" Extension, Aluminum with Assist			
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback			
Vents	Sidewall Airflow			
Fenders	Aluminum Treadplate			
Axle	(2) 5200 lb. Drop Spring Brake			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST225/75R15D 8-PR			
Wheels	15", 6-Hole Steel			
Exterior Finish	.030" Aluminum			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop			
Roof	Flat Top Seamless Aluminum			
Interior Walls	Engineered Wood			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Lauan Strip			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) LED			
Switches	(1) Dome Light, 12V			
Connector Plug	Round 7-pin Blade			
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.