

	8.5 x 36	8.5 x 38
Model #	K10236VSFBGNCH-150	K10238VSFBGNCH-150
CAPACITIES		
GVWR (lbs)	15000	
GAWR (lbs/axle)	5000	
CHASSIS		
Frame	8" x 2" Steel Tube	
Tongue	Gooseneck	
Crossmembers	Formed Steel, 16" On-Center	
Integrated Step(s)	Interior Recessed	
Coupler	2-5/16" Gooseneck	
Safety Chains	DOT Compliant	
Tongue Jack	Dual 12K, 2-Speed Landing Gear	
Wall Studs	Steel Tube, 16" On-Center	
Roof Bows	Steel Tube, 16" On-Center	
Front Profile	Flat	
Beavertail	48"	
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist	
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback	
Access Doors	16" x 48" in Riser	
Vents	Sidewall Airflow	
Fenders	Smooth Aluminum	
Axle	(3) 5200 lb. Drop Spring Brake	
Hubs	Easy Lube	
Breakaway	Battery, Switch, and Lanyard	
Tires	ST225/75R15D 8-PR	
Wheels	15", 6-Hole Aluminum	
Exterior Finish	.030" Aluminum	
Undercoating	Automotive	
Exterior Fastening	VHB Bonded (Screwless)	
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop	
Roof	Flat Top Seamless Aluminum	
Interior Walls	9mm White Vinyl	
Interior Trim	Extruded Aluminum Wall Transitions	
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves	
Flooring	3/4" Engineered Wood	
Interior Lights	(2) LED	
Switches	(1) Dome Light, 12V	
Cargo Control	(4) 5000 lb. Recessed D-Rings	
Connector Plug	Round 7-pin Blade	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION GOOSENECK CAR HAULER VISION FLAT TOP FLAT FRONT 15K

8.5 x 36

8.5 x 38

Exterior Lights

Full LED, DOT Compliant, Integrated Backup/Taillights

DIMENSIONS

Overall Length

440"

464"

Deck Length

433"

457"

Deck Width

96.88"

Deck Height

23.75"



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10228VSFBGNCH-160	K10230VSFBGNCH-160	K10232VSFBGNCH-160	K10234VSFBGNCH-160
CAPACITIES				
GVWR (lbs)	16000			
GAWR (lbs/axle)	8000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	Gooseneck			
Crossmembers	Formed Steel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Gooseneck			
Safety Chains	DOT Compliant			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	48"			
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist			
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	16" x 48" in Riser			
Vents	Sidewall Airflow			
Fenders	Smooth Aluminum			
Axle	(2) 8000 lb. Drop Spring Brake			
Hubs	Oil Bath			
Breakaway	Battery, Switch, and Lanyard			
Tires	215/75R17.5J 18-PR			
Wheels	17.5", 8-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop			
Roof	Flat Top Seamless Aluminum			
Interior Walls	9mm White Vinyl			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) LED			
Switches	(1) Dome Light, 12V			
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION GOOSENECK CAR HAULER VISION FLAT TOP FLAT FRONT 16K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			
DIMENSIONS				
Overall Length	344"			
Deck Length	337"			
Deck Width	96.88"			
Deck Height	25.25"			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Model #	K10240VSFBGNCH-210	K10242VSFBGNCH-210	K10244VSFBGNCH-210	K10246VSFBGNCH-210	K10248VSFBGNCH-210	K10250VSFBGNCH-210
CAPACITIES						
GVWR (lbs)	21000					
GAWR (lbs/axle)	7000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	Gooseneck					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Gooseneck					
Safety Chains	DOT Compliant					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	48"					
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Access Doors	16" x 48" in Riser					
Vents	Sidewall Airflow					
Fenders	Smooth Aluminum					
Axle	(3) 7000 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Interior Walls	9mm White Vinyl					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION GOOSENECK CAR HAULER VISION FLAT TOP FLAT FRONT 21K

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
DIMENSIONS						
Overall Length	488"	512"	536"	560"	584"	608"
Deck Length	481"	505"	529"	553"	577"	601"
Deck Width	96.88"					
Deck Height	25.25"					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 52	
Model #	K10252VSFBGNCH-210
CAPACITIES	
GVWR (lbs)	21000
GAWR (lbs/axle)	7000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	Sidewall Airflow
Fenders	Smooth Aluminum
Axle	(3) 7000 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST235/80R16E 10-PR
Wheels	16", 8-Hole Aluminum
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop
Roof	Flat Top Seamless Aluminum
Interior Walls	9mm White Vinyl
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights
DIMENSIONS	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**VISION GOOSENECK CAR HAULER
VISION FLAT TOP FLAT FRONT 21K**

8.5 x 52	
Overall Length	632"
Deck Length	625"
Deck Width	96.88"
Deck Height	25.25"



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Model #	K10240VSFBGNCH-240	K10242VSFBGNCH-240	K10244VSFBGNCH-240	K10246VSFBGNCH-240	K10248VSFBGNCH-240	K10250VSFBGNCH-240
CAPACITIES						
GVWR (lbs)	24000					
GAWR (lbs/axle)	8000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	Gooseneck					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Gooseneck					
Safety Chains	DOT Compliant					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	48"					
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Access Doors	16" x 48" in Riser					
Vents	Sidewall Airflow					
Fenders	Smooth Aluminum					
Axle	(3) 8000 lb. Drop Spring Brake					
Hubs	Oil Bath					
Breakaway	Battery, Switch, and Lanyard					
Tires	215/75R17.5J 18-PR					
Wheels	17.5", 8-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Interior Walls	9mm White Vinyl					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

8.5 x 52	
Model #	K10252VSFBGNCH-240
CAPACITIES	
GVWR (lbs)	24000
GAWR (lbs/axle)	8000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	Sidewall Airflow
Fenders	Smooth Aluminum
Axle	(3) 8000 lb. Drop Spring Brake
Hubs	Oil Bath
Breakaway	Battery, Switch, and Lanyard
Tires	215/75R17.5J 18-PR
Wheels	17.5", 8-Hole Aluminum
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop
Roof	Flat Top Seamless Aluminum
Interior Walls	9mm White Vinyl
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10228VSFBGNCH-100	K10230VSFBGNCH-100	K10232VSFBGNCH-100	K10234VSFBGNCH-100
CAPACITIES				
GVWR (lbs)	9900			
GAWR (lbs/axle)	5000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	Gooseneck			
Crossmembers	Formed Steel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Gooseneck			
Safety Chains	DOT Compliant			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	48"			
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist			
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	16" x 48" in Riser			
Vents	Sidewall Airflow			
Fenders	Smooth Aluminum			
Axle	(2) 5200 lb. Drop Spring Brake			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST225/75R15D 8-PR			
Wheels	15", 6-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop			
Roof	Flat Top Seamless Aluminum			
Interior Walls	9mm White Vinyl			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) LED			
Switches	(1) Dome Light, 12V			
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION GOOSENECK CAR HAULER VISION FLAT TOP FLAT FRONT 10K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			
DIMENSIONS				
Overall Length	344"	368"	392"	416"
Deck Length	337"	361"	385"	409"
Deck Width	96.88"			
Deck Height	23.75"			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10228VSFBGNCH-140	K10230VSFBGNCH-140	K10232VSFBGNCH-140	K10234VSFBGNCH-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	Gooseneck			
Crossmembers	Formed Steel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Gooseneck			
Safety Chains	DOT Compliant			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	48"			
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist			
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	16" x 48" in Riser			
Vents	Sidewall Airflow			
Fenders	Smooth Aluminum			
Axle	(2) 7000 lb. Drop Spring Brake			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST235/80R16E 10-PR			
Wheels	16", 8-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop			
Roof	Flat Top Seamless Aluminum			
Interior Walls	9mm White Vinyl			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) LED			
Switches	(1) Dome Light, 12V			
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION GOOSENECK CAR HAULER VISION FLAT TOP FLAT FRONT 14K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			
DIMENSIONS				
Overall Length	344"		392"	
Deck Length	337"		385"	
Deck Width	96.88"		96.88"	
Deck Height	25.25"		25.25"	



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.