

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34					
Model #	K10228VSFBGN-140	K10230VSFBGN-140	K10232VSFBGN-140	K10234VSFBGN-140					
CAPACITIES									
GVWR (lbs)	14000								
GAWR (lbs/axle)	7000								
CHASSIS		7000							
Frame		0" v 2" C	teel Tube						
Tongue			eneck						
Crossmembers			16" On-Center						
Integrated Step(s)		•	Recessed						
Coupler			ooseneck						
Safety Chains			mpliant						
Tongue Jack			ed Landing Gear						
Wall Studs		•	6" On-Center						
Roof Bows			6" On-Center						
Front Profile		·	at						
Ramp(s)			e Cap, 4000 lb. with Assist						
Side Door			ast Aluminum Holdback						
Access Doors		•	" in Riser						
Vents		Sidewal	l Airflow						
Fenders	Smooth Aluminum								
Axle		(2) 7000 lb. Dro	op Spring Brake						
Hubs		Easy	Lube						
Breakaway		Battery, Switc	h, and Lanyard						
Tires		ST235/80F	R16E 10-PR						
<b>Exterior Finish</b>		.030" Al	uminum						
Undercoating		Autor	notive						
<b>Exterior Fastening</b>		VHB Bonded	l (Screwless)						
Exterior Trim	2.5" Top Extrusion, 3" Botton	n Extrusion, ATP Riser Wall, Brite	e Aluminum Radius Front Corne	ers, Brite Aluminum Rear Hoop					
Roof		Flat Top Seam	less Aluminum						
Interior Walls			red Wood						
Interior Trim			m Wall Transitions						
Ceiling	,	Vinyl Ceiling Transitions, White	· ·	es					
Flooring		•	eered Wood						
Interior Lights		* *	LED						
Switches		· , ,	Light, 12V						
Connector Plug			pin Blade						
Exterior Lights		Full LED, DOT Compliant, Ir	ntegrated Backup/Taillights						
DIMENSIONS									
Overall Length		368"	392"						







	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Deck Length		361"	385"	
Deck Width		96	.88"	
Deck Height		25	5.25"	





	8.5 x 36	8.5 x 38				
Model #	K10236VSFBGN-150	K10238VSFBGN-150				
CAPACITIES						
GVWR (lbs)	15	000				
GAWR (lbs/axle)	50	000				
CHASSIS						
Frame	8" x 2" S	iteel Tube				
Tongue	Goos	eneck				
Crossmembers	Formed Steel,	, 16" On-Center				
Integrated Step(s)	Interior	Recessed				
Coupler	2-5/16" 0	Gooseneck				
Safety Chains	DOT Co	ompliant				
Tongue Jack	Dual 12K, 2-Spe	eed Landing Gear				
Wall Studs	Steel Tube,	16" On-Center				
Roof Bows	Steel Tube,	16" On-Center				
Front Profile	F	lat				
Ramp(s)	12" Extension with Bullnos	se Cap, 4000 lb. with Assist				
Side Door	36" Wide Flush Lock, C	ast Aluminum Holdback				
Access Doors	16" x 48	" in Riser				
Vents	Sidewa	ll Airflow				
Fenders	Smooth A	Aluminum				
Axle	(3) 5200 lb. Dr	op Spring Brake				
Hubs	Easy	Lube				
Breakaway	Battery, Switc	h, and Lanyard				
Tires	ST225/75	R15D 8-PR				
<b>Exterior Finish</b>	.030" A	luminum				
Undercoating	Auto	motive				
<b>Exterior Fastening</b>	VHB Bonded	d (Screwless)				
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brit	e Aluminum Radius Front Corners, Brite Aluminum Rear Hoop				
Roof	Flat Top Seam	less Aluminum				
Interior Walls	<u> </u>	red Wood				
Interior Trim		ım Wall Transitions				
Ceiling	• •	Vinyl Liner with Aluminum Coves				
Flooring	<del>_</del>	eered Wood				
Interior Lights	(2)	LED				
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, I	ntegrated Backup/Taillights				
DIMENSIONS						
Overall Length	440"	464"				







	8.5 x 36	8.5 x 38
Deck Length	433"	457"
Deck Width	96.	.88"
Deck Height	23.	.75"





	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34						
Model #	K10228VSFBGN-160	K10230VSFBGN-160	K10232VSFBGN-160	K10234VSFBGN-160						
CAPACITIES										
GVWR (lbs)		16000								
GAWR (lbs/axle)		80	000							
CHASSIS										
Frame		8" x 2" Steel Tube								
Tongue		Goos	eneck							
Crossmembers		Formed Steel,	, 16" On-Center							
Integrated Step(s)		Interior	Recessed							
Coupler		2-5/16" 0	Gooseneck							
Safety Chains		DOT Co	ompliant							
Tongue Jack		Dual 12K, 2-Spe	eed Landing Gear							
Wall Studs		Steel Tube,	16" On-Center							
Roof Bows		Steel Tube, 1	16" On-Center							
Front Profile		F	lat							
Ramp(s)		12" Extension with Bullnos	se Cap, 4000 lb. with Assist							
Side Door		36" Wide Flush Lock, C	ast Aluminum Holdback							
Access Doors		16" x 48	" in Riser							
Vents		Sidewa	ll Airflow							
Fenders		Smooth A	Aluminum							
Axle		(2) 8000 lb. Dr	op Spring Brake							
Hubs		Oil	Bath							
Breakaway		Battery, Switc	h, and Lanyard							
Tires		215/75R1	7.5J 18-PR							
Exterior Finish		.030" A	luminum							
Undercoating		Auto	motive							
Exterior Fastening		VHB Bonded	d (Screwless)							
Exterior Trim	2.5" Top Extrusion, 3" Bottom	Extrusion, ATP Riser Wall, Brit	e Aluminum Radius Front Corne	ers, Brite Aluminum Rear Hoo						
Roof		Flat Top Seam	less Aluminum							
Interior Walls		Enginee	red Wood							
Interior Trim		Extruded Aluminu	ım Wall Transitions							
Ceiling	1	/inyl Ceiling Transitions, White	Vinyl Liner with Aluminum Cove	es						
Flooring		3/4" Engin	eered Wood							
Interior Lights		(2) LED								
Switches		(1) Dome	Light, 12V							
Connector Plug		Round 7	-pin Blade							
Exterior Lights		Full LED, DOT Compliant, I	ntegrated Backup/Taillights							
DIMENSIONS										
Overall Length	344"	368"								



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

2025 Pricing





	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Deck Length	337"	361"		
Deck Width	96.88"			
Deck Height	25.25"			





	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50			
	K10240VSFBGN-	K10242VSFBGN-	K10244VSFBGN-	K10246VSFBGN-	K10248VSFBGN-	K10250VSFBGN-			
Model #	210	210	210	210	210	210			
CAPACITIES									
GVWR (lbs)		21000							
GAWR (lbs/axle)				100					
CHASSIS									
Frame			Q" v 2" C	teel Tube					
Tongue				eneck					
Crossmembers				16" On-Center					
Integrated Step(s)			•	Recessed					
Coupler				ooseneck					
Safety Chains				mpliant					
Tongue Jack				ed Landing Gear					
Wall Studs			Steel Tube, 1	6" On-Center					
<b>Roof Bows</b>			Steel Tube, 1	6" On-Center					
Front Profile			F	at					
Ramp(s)		12" E	xtension with Bullnos	e Cap, 4000 lb. with	Assist				
Side Door		36	" Wide Flush Lock, C	ast Aluminum Holdba	ack				
Access Doors			16" x 48	" in Riser					
Vents			Sidewal	l Airflow					
Fenders			Smooth A	Aluminum					
Axle			• • • • • • • • • • • • • • • • • • • •	op Spring Brake					
Hubs			•	Lube					
Breakaway			•	h, and Lanyard					
Tires				R16E 10-PR					
Exterior Finish				luminum 					
Undercoating				notive					
Exterior Fastening Exterior Trim	2 E" Ton Extrucion	2" Pottom Extrusion	v nb Bonded , ATP Riser Wall, Brite	l (Screwless)	ront Cornera Prita	luminum Door Hoon			
Roof	2.5 Top Extrusion,	5 BULLOIN EXTRUSION		less Aluminum	Tonic Corners, Brite A	iuiiiiiuiii keai rioop			
Interior Walls			•	red Wood					
Interior Trim				m Wall Transitions					
Ceiling		Vinyl Ceilin	g Transitions, White		inum Coves				
Flooring		,	•	eered Wood					
Interior Lights				LED					
Switches			, ,	Light, 12V					
Connector Plug			Round 7-	pin Blade					
Exterior Lights		Full L	ED, DOT Compliant, Ir	ntegrated Backup/Tai	illights				
DIMENSIONS									







	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Overall Length	488"	512"	536"	560"	584"	608"
Deck Length	481"	505"	529"	553"	577"	601"
Deck Width			96.	88"		
Deck Height	25.25"					





	8.5 x 52
Model #	K10252VSFBGN-210
CAPACITIES	
GVWR (lbs)	21000
GAWR (lbs/axle)	7000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
Front Profile	Flat
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	Sidewall Airflow
Fenders	Smooth Aluminum
Axle	(3) 7000 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST235/80R16E 10-PR
Exterior Finish	.030" Aluminum
Undercoating	Automotive
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights
DIMENSIONS	
Overall Length	632"







	8.5 x 52
Deck Length	625"
Deck Width	96.88"
Deck Height	25.25"





	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50			
B.B J I. //	K10240VSFBGN-	K10242VSFBGN-	K10244VSFBGN-	K10246VSFBGN-	K10248VSFBGN-	K10250VSFBGN-			
Model #	240	240	240	240	240	240			
CAPACITIES									
GVWR (lbs)		24000							
GAWR (lbs/axle)			80	000					
CHASSIS									
Frame			8" x 2" S	teel Tube					
Tongue			Goos	eneck					
Crossmembers			Formed Steel,	16" On-Center					
Integrated Step(s)			Interior I	Recessed					
Coupler			2-5/16" G	ooseneck					
Safety Chains			DOT Co	mpliant					
Tongue Jack			Dual 12K, 2-Spe	ed Landing Gear					
Wall Studs			Steel Tube, 1	6" On-Center					
Roof Bows			Steel Tube, 1	6" On-Center					
Front Profile			F	at					
Ramp(s)		12" E	xtension with Bullnos	e Cap, 4000 lb. with	Assist				
Side Door		36	5" Wide Flush Lock, C	ast Aluminum Holdba	ack				
Access Doors			16" x 48	" in Riser					
Vents			Sidewal	l Airflow					
Fenders			Smooth A	Aluminum					
Axle			(3) 8000 lb. Dr	op Spring Brake					
Hubs			Oil	Bath					
Breakaway			Battery, Switc	h, and Lanyard					
Tires			215/75R1	7.5J 18-PR					
<b>Exterior Finish</b>			.030" A	luminum					
Undercoating			Autor	notive					
Exterior Fastening			VHB Bonded	l (Screwless)					
Exterior Trim	2.5" Top Extrusion,	3" Bottom Extrusion	, ATP Riser Wall, Brite	e Aluminum Radius F	ront Corners, Brite A	uminum Rear Hoop			
Roof			Flat Top Seam	less Aluminum					
Interior Walls				red Wood					
Interior Trim				m Wall Transitions					
Ceiling		Vinyl Ceilin	ng Transitions, White	•	ninum Coves				
Flooring				eered Wood					
Interior Lights			, ,	LED					
Switches			, ,	Light, 12V					
Connector Plug				pin Blade					
Exterior Lights		Full L	ED, DOT Compliant, I	ntegrated Backup/Ta	illights				
DIMENSIONS									







	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Overall Length	488"	512"	536"	560"		
Deck Length	481"	505"	529"	553"		
Deck Width		96.88"				
Deck Height		25.				





	8.5 x 52				
Model #	K10252VSFBGN-240				
CAPACITIES					
GVWR (lbs)	24000				
GAWR (lbs/axle)	8000				
CHASSIS					
Frame _	8" x 2" Steel Tube				
Tongue	Gooseneck				
Crossmembers	Formed Steel, 16" On-Center				
Integrated Step(s)	Interior Recessed				
Coupler	2-5/16" Gooseneck				
Safety Chains	DOT Compliant				
Tongue Jack	Dual 12K, 2-Speed Landing Gear				
Wall Studs	Steel Tube, 16" On-Center				
Roof Bows	Steel Tube, 16" On-Center				
Front Profile	Flat				
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist				
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback 16" x 48" in Riser				
Access Doors	Sidewall Airflow				
Vents	Sidewall Airnow Smooth Aluminum				
Fenders Axle					
Hubs	(3) 8000 lb. Drop Spring Brake Oil Bath				
Breakaway Tires	Battery, Switch, and Lanyard				
Exterior Finish	215/75R17.5J 18-PR				
Undercoating	.030" Aluminum				
Exterior Fastening	Automotive  VHB Bonded (Screwless)				
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop				
Roof	Flat Top Seamless Aluminum				
Interior Walls	Engineered Wood				
Interior Trim	Extruded Aluminum Wall Transitions				
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves				
Flooring	3/4" Engineered Wood				
Interior Lights	(2) LED				
Switches	(1) Dome Light, 12V				
Connector Plug	Round 7-pin Blade				
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights				
_					





	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34		
Model #	K10228VSFBGN-100	K10230VSFBGN-100	K10232VSFBGN-100	K10234VSFBGN-100		
CAPACITIES						
GVWR (lbs)		00	00			
GAWR (lbs/axle)						
CHASSIS	5000					
000.0						
Frame _	8" x 2" Steel Tube					
Tongue	Gooseneck Formed Steel, 16" On-Center					
Crossmembers		•				
Integrated Step(s)			Recessed			
Coupler	2-5/16" Gooseneck					
Safety Chains	DOT Compliant					
Tongue Jack Wall Studs	Dual 12K, 2-Speed Landing Gear					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Steel Tube, 16" On-Center					
Ramp(s)	Flat					
Side Door	12" Extension with Bullnose Cap, 4000 lb. with Assist 36" Wide Flush Lock, Cast Aluminum Holdback					
Access Doors		·				
Vents	16" x 48" in Riser Sidewall Airflow					
Fenders	Sidewall Airtiow Smooth Aluminum					
Axle	Smooth Aluminum  (2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, ATP Riser Wall, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					
DIMENSIONS						
Overall Length	344"	368"	392"	416"		



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

© 2025 Novae LLC





	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34		
Deck Length	337"	361"	385"	409"		
Deck Width	96.88"					
Deck Height	23.75"					

