

	8.5 x 17	8.5 x 19	8.5 x 21	8.5 x 23	8.5 x 25	8.5 x 27
Model #	K10217VSFVMS-070	K10219VSFVMS-070	K10221VSFVMS-070	K10223VSFVMS-070	K10225VSFVMS-070	K10227VSFVMS-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Tube with Center Drawbar, Max Extension					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable, Equalizer Brackets					
Safety Chains	DOT Compliant					
Tongue Jack	5K Drop Leg, Frame Mounted					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	60" Aero Wedge					
Beavertail			32"		48"	
Ramp(s)	16" Extension with Bullnose Cap (Both Ramps), 4000 lb. with Assist, 72" Front Wedge Wrap Around with Assist, Traction Bars (Both Ramps)					
Side Door		24" Wide Flush Lock, Cast Aluminum Holdback		36" Wide Flush Lock, Cast Aluminum Holdback		
Access Doors	14" x 14" Fuel					
Vents	Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 3500 lb. Torsion Brake, (45° Down), Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Interior Walls	9mm White Vinyl					
Interior Trim	ATP Kickplate, 12" Tall, Vinyl Wall Transitions					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 17	8.5 x 19	8.5 x 21	8.5 x 23	8.5 x 25	8.5 x 27
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Poly-Tread Laminate					
Wheel Box	6" Tapered Drive-over					
Interior Lights	(2) 11" LED					
Switches	(1) Dome Light, 12V, (2) Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings, Xtreme Slide Track with (8) D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(1) Front LED Loading, (2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					

	8.5 x 29	8.5 x 31	8.5 x 33	8.5 x 35	8.5 x 37
Model #	K10229VSFVMS-070	K10231VSFVMS-070	K10233VSFVMS-070	K10235VSFVMS-070	K10237VSFVMS-070
CAPACITIES					
GVWR (lbs)	7000				
GAWR (lbs/axle)	3500				
CHASSIS					
Frame	6" x 2" Steel Tube		8" x 2" Steel Tube		
Tongue	6" x 2" Steel Tube with Center Drawbar, Max Extension		8" x 2" Steel Tube with Center Drawbar, Max Extension		
Crossmembers	Formed Steel, 16" On-Center				
Integrated Step(s)	Interior Recessed				
Coupler	2-5/16" Adjustable, Equalizer Brackets				
Safety Chains	DOT Compliant				
Tongue Jack	5K Drop Leg, Frame Mounted				
Wall Studs	Steel Tube, 16" On-Center				
Roof Bows	Steel Tube, 16" On-Center				
Front Profile	60" Aero Wedge				
Beavertail	48"				
Ramp(s)	16" Extension with Bullnose Cap (Both Ramps), 4000 lb. with Assist, 72" Front Wedge Wrap Around with Assist, Traction Bars (Both Ramps)				
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback				
Access Doors	14" x 14" Fuel				
Vents	Sidewall Airflow				
Fenders	Extruded Aluminum				
Axle	(2) 3500 lb. Torsion Brake, (45° Down), Spread Axle Configuration				
Hubs	Easy Lube				
Breakaway	Battery, Switch, and Lanyard				
Tires	ST205/75R15C 6-PR				
Wheels	15", 5-Hole Aluminum				
Exterior Finish	.030" Aluminum				
Undercoating	Automotive				
Exterior Fastening	VHB Bonded (Screwless)				
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop				
Stone Guard	24" ATP				
Rear Spoiler	9" Brite Aluminum Flare				
Roof	Flat Top Seamless Aluminum				
Interior Walls	9mm White Vinyl				
Interior Trim	ATP Kickplate, 12" Tall, Vinyl Wall Transitions				
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves				
Flooring	3/4" Poly-Tread Laminate				
Wheel Box	6" Tapered Drive-over				

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 29	8.5 x 31	8.5 x 33	8.5 x 35	8.5 x 37
Interior Lights	(2) 11" LED				
Switches	(1) Dome Light, 12V, (2) Load Light, 12V				
Cargo Control	(4) 5000 lb. Recessed D-Rings, Xtreme Slide Track with (8) D-Rings				
Connector Plug	Round 7-pin Blade				
Exterior Lights	(1) Front LED Loading, (2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights				

	8.5 x 17	8.5 x 19	8.5 x 21	8.5 x 23	8.5 x 25	8.5 x 27
Model #	K10217VSFVMS-100	K10219VSFVMS-100	K10221VSFVMS-100	K10223VSFVMS-100	K10225VSFVMS-100	K10227VSFVMS-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Tube with Center Drawbar, Max Extension					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable, Equalizer Brackets					
Safety Chains	DOT Compliant					
Tongue Jack	5K Drop Leg, Frame Mounted					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	60" Aero Wedge					
Beavertail			32"		48"	
Ramp(s)	16" Extension with Bullnose Cap (Both Ramps), 4000 lb. with Assist, 72" Front Wedge Wrap Around with Assist, Traction Bars (Both Ramps)					
Side Door		24" Wide Flush Lock, Cast Aluminum Holdback		36" Wide Flush Lock, Cast Aluminum Holdback		
Access Doors	14" x 14" Fuel					
Vents	Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 5200 lb. Torsion Brake, (45° Down), Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Interior Walls	9mm White Vinyl					
Interior Trim	ATP Kickplate, 12" Tall, Vinyl Wall Transitions					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 17	8.5 x 19	8.5 x 21	8.5 x 23	8.5 x 25	8.5 x 27
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Poly-Tread Laminate					
Wheel Box	6" Tapered Drive-over					
Interior Lights	(2) 11" LED					
Switches	(1) Dome Light, 12V, (2) Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings, Xtreme Slide Track with (8) D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(1) Front LED Loading, (2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					

	8.5 x 29	8.5 x 31	8.5 x 33	8.5 x 35	8.5 x 37
Model #	K10229VSFVMS-100	K10231VSFVMS-100	K10233VSFVMS-100	K10235VSFVMS-100	K10237VSFVMS-100
CAPACITIES					
GVWR (lbs)	9900				
GAWR (lbs/axle)	5000				
Curb Weight	4760				
Payload	5140				
CHASSIS					
Frame	6" x 2" Steel Tube		8" x 2" Steel Tube		
Tongue	6" x 2" Steel Tube with Center Drawbar, Max Extension		8" x 2" Steel Tube with Center Drawbar, Max Extension		
Crossmembers	Formed Steel, 16" On-Center				
Integrated Step(s)	Interior Recessed				
Coupler	2-5/16" Adjustable, Equalizer Brackets				
Safety Chains	DOT Compliant				
Tongue Jack	5K Drop Leg, Frame Mounted				
Wall Studs	Steel Tube, 16" On-Center				
Roof Bows	Steel Tube, 16" On-Center				
Front Profile	60" Aero Wedge				
Beavertail	48"				
Ramp(s)	16" Extension with Bullnose Cap (Both Ramps), 4000 lb. with Assist, 72" Front Wedge Wrap Around with Assist, Traction Bars (Both Ramps)				
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback				
Access Doors	14" x 14" Fuel				
Vents	Sidewall Airflow				
Fenders	Extruded Aluminum				
Axle	(2) 5200 lb. Torsion Brake, (45° Down), Spread Axle Configuration				
Hubs	Easy Lube				
Breakaway	Battery, Switch, and Lanyard				
Tires	ST225/75R15D 8-PR				
Wheels	15", 6-Hole Aluminum				
Exterior Finish	.030" Aluminum				
Undercoating	Automotive				
Exterior Fastening	VHB Bonded (Screwless)				
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop				
Stone Guard	24" ATP				
Rear Spoiler	9" Brite Aluminum Flare				
Roof	Flat Top Seamless Aluminum				
Interior Walls	9mm White Vinyl				
Interior Trim	ATP Kickplate, 12" Tall, Vinyl Wall Transitions				
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves				

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**VISION PURESORT MOTORSPORT
VISION FLAT TOP AERO WEDGE 10K**

	8.5 x 29	8.5 x 31	8.5 x 33	8.5 x 35	8.5 x 37
Flooring	3/4" Poly-Tread Laminate				
Wheel Box	6" Tapered Drive-over				
Interior Lights	(2) 11" LED				
Switches	(1) Dome Light, 12V, (2) Load Light, 12V				
Cargo Control	(4) 5000 lb. Recessed D-Rings, Xtreme Slide Track with (8) D-Rings				
Connector Plug	Round 7-pin Blade				
Exterior Lights	(1) Front LED Loading, (2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights				



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 17	8.5 x 19	8.5 x 21	8.5 x 23	8.5 x 25	8.5 x 27
Model #	K10217VSFVMS-140	K10219VSFVMS-140	K10221VSFVMS-140	K10223VSFVMS-140	K10225VSFVMS-140	K10227VSFVMS-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	8" x 2" Steel Tube with Center Drawbar, Max Extension					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable, Equalizer Brackets					
Safety Chains	DOT Compliant					
Tongue Jack	5K Drop Leg, Frame Mounted					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	60" Aero Wedge					
Beavertail			32"		48"	
Ramp(s)	16" Extension with Bullnose Cap (Both Ramps), 4000 lb. with Assist, 72" Front Wedge Wrap Around with Assist, Traction Bars (Both Ramps)					
Side Door		24" Wide Flush Lock, Cast Aluminum Holdback	36" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	14" x 14" Fuel					
Vents	Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 7000 lb. Torsion Brake, (45° Down), Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Interior Walls	9mm White Vinyl					
Interior Trim	ATP Kickplate, 12" Tall, Vinyl Wall Transitions					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 17	8.5 x 19	8.5 x 21	8.5 x 23	8.5 x 25	8.5 x 27
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Poly-Tread Laminate					
Wheel Box	6" Tapered Drive-over					
Interior Lights	(2) 11" LED					
Switches	(1) Dome Light, 12V, (2) Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings, Xtreme Slide Track with (8) D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(1) Front LED Loading, (2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					

	8.5 x 29	8.5 x 31	8.5 x 33	8.5 x 35	8.5 x 37
Model #	K10229VSFVMS-140	K10231VSFVMS-140	K10233VSFVMS-140	K10235VSFVMS-140	K10237VSFVMS-140
CAPACITIES					
GVWR (lbs)	14000				
GAWR (lbs/axle)	7000				
CHASSIS					
Frame	8" x 2" Steel Tube				
Tongue	8" x 2" Steel Tube with Center Drawbar, Max Extension				
Crossmembers	Formed Steel, 16" On-Center				
Integrated Step(s)	Interior Recessed				
Coupler	2-5/16" Adjustable, Equalizer Brackets				
Safety Chains	DOT Compliant				
Tongue Jack	5K Drop Leg, Frame Mounted				
Wall Studs	Steel Tube, 16" On-Center				
Roof Bows	Steel Tube, 16" On-Center				
Front Profile	60" Aero Wedge				
Beavertail	48"				
Ramp(s)	16" Extension with Bullnose Cap (Both Ramps), 4000 lb. with Assist, 72" Front Wedge Wrap Around with Assist, Traction Bars (Both Ramps)				
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback				
Access Doors	14" x 14" Fuel				
Vents	Sidewall Airflow				
Fenders	Extruded Aluminum				
Axle	(2) 7000 lb. Torsion Brake, (45° Down), Spread Axle Configuration				
Hubs	Easy Lube				
Breakaway	Battery, Switch, and Lanyard				
Tires	ST235/80R16E 10-PR				
Wheels	16", 8-Hole Aluminum				
Exterior Finish	.030" Aluminum				
Undercoating	Automotive				
Exterior Fastening	VHB Bonded (Screwless)				
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop				
Stone Guard	24" ATP				
Rear Spoiler	9" Brite Aluminum Flare				
Roof	Flat Top Seamless Aluminum				
Interior Walls	9mm White Vinyl				
Interior Trim	ATP Kickplate, 12" Tall, Vinyl Wall Transitions				
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Covers				
Flooring	3/4" Poly-Tread Laminate				
Wheel Box	6" Tapered Drive-over				
Interior Lights	(2) 11" LED				

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION PURESPORT MOTORSPORT VISION FLAT TOP AERO WEDGE 14K

	8.5 x 29	8.5 x 31	8.5 x 33	8.5 x 35	8.5 x 37
Switches	(1) Dome Light, 12V, (2) Load Light, 12V				
Cargo Control	(4) 5000 lb. Recessed D-Rings, Xtreme Slide Track with (8) D-Rings				
Connector Plug	Round 7-pin Blade				
Exterior Lights	(1) Front LED Loading, (2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights				



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.