

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	K10216VSFBRT-140	K10218VSFBRT-140	K10220VSFBRT-140	K10222VSFBRT-140	K10224VSFBRT-140	K10226VSFBRT-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	6" Extension, 8" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	32"				48"	
Ramp(s)	16" Extension, 4000 lb. with Assist					
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Roof Vent Frame, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 7000 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop, Polished Cast Aluminum Roof Corners					
Stone Guard	24" ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Brite Aluminum					
Interior Walls	9mm White Vinyl					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Interior Lights	(2) 11" LED					
Switches	(1) Dome Light, 12V, (1) Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
DIMENSIONS						
Overall Length	257"	281"	305"	329"	353"	377"
Deck Length	187"	211"	235"	259"	283"	307"
Deck Width	96.88"					
Deck Height	25.25"					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10228VSFBRT-140	K10230VSFBRT-140	K10232VSFBRT-140	K10234VSFBRT-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	6" Extension, 8" x 2" Steel Triple Tube			
Crossmembers	Formed Steel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Adjustable			
Safety Chains	DOT Compliant			
Tongue Jack	7K Drop Leg, Set-Back			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	48"			
Ramp(s)	16" Extension, 4000 lb. with Assist			
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback			
Vents	Roof Vent Frame, Sidewall Airflow			
Fenders	Extruded Aluminum			
Axle	(2) 7000 lb. Torsion Brake, Spread Axle Configuration			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST235/80R16E 10-PR			
Wheels	16", 8-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop, Polished Cast Aluminum Roof Corners			
Stone Guard	24" ATP			
Rear Spoiler	9" Brite Aluminum Flare			
Roof	Flat Top Seamless Aluminum			
Roof Cap	Brite Aluminum			
Interior Walls	9mm White Vinyl			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) 11" LED			
Switches	(1) Dome Light, 12V, (1) Load Light, 12V			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION RACE
VISION FLAT TOP FLAT FRONT 14K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights			
DIMENSIONS				
Overall Length	401"	425"	449"	473"
Deck Length	331"	355"	379"	403"
Deck Width	96.88"			
Deck Height	25.25"			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10228VSFBRT-150	K10230VSFBRT-150	K10232VSFBRT-150	K10234VSFBRT-150
CAPACITIES				
GVWR (lbs)	15000			
GAWR (lbs/axle)	5000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	6" Extension, 8" x 2" Steel Triple Tube			
Crossmembers	Formed Steel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Adjustable			
Safety Chains	DOT Compliant			
Tongue Jack	7K Drop Leg, Set-Back			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	48"			
Ramp(s)	16" Extension, 4000 lb. with Assist			
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback			
Vents	Roof Vent Frame, Sidewall Airflow			
Fenders	Extruded Aluminum			
Axle	(3) 5200 lb. Torsion Brake, Spread Axle Configuration			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST225/75R15D 8-PR			
Wheels	15", 6-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop, Polished Cast Aluminum Roof Corners			
Stone Guard	24" ATP			
Rear Spoiler	9" Brite Aluminum Flare			
Roof	Flat Top Seamless Aluminum			
Roof Cap	Brite Aluminum			
Interior Walls	9mm White Vinyl			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Covers			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) 11" LED			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Switches	(1) Dome Light, 12V, (1) Load Light, 12V			
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights			
DIMENSIONS				
Overall Length	401"	425"	449"	473"
Deck Length	331"	355"	379"	403"
Deck Width	96.88"			
Deck Height	23.75"			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
Model #	K10220VSFBRT-160	K10222VSFBRT-160	K10224VSFBRT-160	K10226VSFBRT-160	K10228VSFBRT-160	K10230VSFBRT-160
CAPACITIES						
GVWR (lbs)	16000					
GAWR (lbs/axle)	8000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	6" Extension, 8" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	12K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	48"					
Ramp(s)	16" Extension, 4000 lb. with Assist					
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Roof Vent Frame, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 8000 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Oil Bath					
Breakaway	Battery, Switch, and Lanyard					
Tires	215/75R17.5J 18-PR					
Wheels	17.5", 8-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop, Polished Cast Aluminum Roof Corners					
Stone Guard	24" ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Brite Aluminum					
Interior Walls	9mm White Vinyl					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
Interior Lights	(2) 11" LED					
Switches	(1) Dome Light, 12V, (1) Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
DIMENSIONS						
Overall Length	305"	329"	353"	377"	401"	425"
Deck Length	235"	259"	283"	307"	331"	355"
Deck Width	96.88"					
Deck Height	25.25"					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 32	8.5 x 34
Model #	K10232VSFBRT-160	K10234VSFBRT-160
CAPACITIES		
GVWR (lbs)	16000	
GAWR (lbs/axle)	8000	
CHASSIS		
Frame	8" x 2" Steel Tube	
Tongue	6" Extension, 8" x 2" Steel Triple Tube	
Crossmembers	Formed Steel, 16" On-Center	
Integrated Step(s)	Interior Recessed	
Coupler	2-5/16" Adjustable	
Safety Chains	DOT Compliant	
Tongue Jack	12K Drop Leg, Set-Back	
Wall Studs	Steel Tube, 16" On-Center	
Roof Bows	Steel Tube, 16" On-Center	
Front Profile	Flat	
Beavertail	48"	
Ramp(s)	16" Extension, 4000 lb. with Assist	
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback	
Vents	Roof Vent Frame, Sidewall Airflow	
Fenders	Extruded Aluminum	
Axle	(2) 8000 lb. Torsion Brake, Spread Axle Configuration	
Hubs	Oil Bath	
Breakaway	Battery, Switch, and Lanyard	
Tires	215/75R17.5J 18-PR	
Wheels	17.5", 8-Hole Aluminum	
Exterior Finish	.030" Aluminum	
Undercoating	Automotive	
Exterior Fastening	VHB Bonded (Screwless)	
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop, Polished Cast Aluminum Roof Corners	
Stone Guard	24" ATP	
Rear Spoiler	9" Brite Aluminum Flare	
Roof	Flat Top Seamless Aluminum	
Roof Cap	Brite Aluminum	
Interior Walls	9mm White Vinyl	
Interior Trim	Extruded Aluminum Wall Transitions	
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves	
Flooring	3/4" Engineered Wood	
Interior Lights	(2) 11" LED	
Switches	(1) Dome Light, 12V, (1) Load Light, 12V	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 32	8.5 x 34
Cargo Control	(4) 5000 lb. Recessed D-Rings	
Connector Plug	Round 7-pin Blade	
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights	
DIMENSIONS		
Overall Length	449"	473"
Deck Length	379"	403"
Deck Width	96.88"	
Deck Height	25.25"	

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	K10228VSFBRT-210	K10230VSFBRT-210	K10232VSFBRT-210	K10234VSFBRT-210
CAPACITIES				
GVWR (lbs)	21000			
GAWR (lbs/axle)	7000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	6" Extension, 8" x 2" Steel Triple Tube			
Crossmembers	Formed Steel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Adjustable			
Safety Chains	DOT Compliant			
Tongue Jack	12K Drop Leg, Set-Back			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Beavertail	48"			
Ramp(s)	16" Extension, 4000 lb. with Assist			
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback			
Vents	Roof Vent Frame, Sidewall Airflow			
Fenders	Extruded Aluminum			
Axle	(3) 7000 lb. Torsion Brake, Spread Axle Configuration			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST235/80R16E 10-PR			
Wheels	16", 8-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop, Polished Cast Aluminum Roof Corners			
Stone Guard	24" ATP			
Rear Spoiler	9" Brite Aluminum Flare			
Roof	Flat Top Seamless Aluminum			
Roof Cap	Brite Aluminum			
Interior Walls	9mm White Vinyl			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Covers			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) 11" LED			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



VISION RACE
VISION FLAT TOP FLAT FRONT 21K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Switches	(1) Dome Light, 12V, (1) Load Light, 12V			
Cargo Control	(4) 5000 lb. Recessed D-Rings			
Connector Plug	Round 7-pin Blade			
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights			
DIMENSIONS				
Overall Length	401"	425"	449"	473"
Deck Length	331"	355"	379"	403"
Deck Width	96.88"			
Deck Height	25.25"			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	K10216VSFBRT-070	K10218VSFBRT-070	K10220VSFBRT-070	K10222VSFBRT-070	K10224VSFBRT-070	K10226VSFBRT-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	32"					48"
Ramp(s)	16" Extension, 4000 lb. with Assist					
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Roof Vent Frame, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 3500 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop, Polished Cast Aluminum Roof Corners					
Stone Guard	24" ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Brite Aluminum					
Interior Walls	9mm White Vinyl					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Interior Lights	(2) 11" LED					
Switches	(1) Dome Light, 12V, (1) Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
DIMENSIONS						
Overall Length		281"	305"	329"	353"	377"
Deck Length		211"	235"	259"	283"	307"
Deck Width		96.88"				
Deck Height		20.75"				

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	K10216VSFBRT-100	K10218VSFBRT-100	K10220VSFBRT-100	K10222VSFBRT-100	K10224VSFBRT-100	K10226VSFBRT-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable					
Safety Chains	DOT Compliant					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Beavertail	32"				48"	
Ramp(s)	16" Extension, 4000 lb. with Assist					
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Roof Vent Frame, Sidewall Airflow					
Fenders	Extruded Aluminum					
Axle	(2) 5200 lb. Torsion Brake, Spread Axle Configuration					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop, Polished Cast Aluminum Roof Corners					
Stone Guard	24" ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Roof Cap	Brite Aluminum					
Interior Walls	9mm White Vinyl					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Interior Lights	(2) 11" LED					
Switches	(1) Dome Light, 12V, (1) Load Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
DIMENSIONS						
Overall Length	257"	281"	305"	329"	353"	377"
Deck Length	187"	211"	235"	259"	283"	307"
Deck Width	96.88"					
Deck Height	21.75"					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 28	8.5 x 30	8.5 x 32
Model #	K10228VSFBRT-100	K10230VSFBRT-100	K10232VSFBRT-100
CAPACITIES			
GVWR (lbs)	9900		
GAWR (lbs/axle)	5000		
CHASSIS			
Frame	8" x 2" Steel Tube		
Tongue	6" Extension, 8" x 2" Steel Triple Tube		
Crossmembers	Formed Steel, 16" On-Center		
Integrated Step(s)	Interior Recessed		
Coupler	2-5/16" Adjustable		
Safety Chains	DOT Compliant		
Tongue Jack	5K Set-Back		
Wall Studs	Steel Tube, 16" On-Center		
Roof Bows	Steel Tube, 16" On-Center		
Front Profile	Flat		
Beavertail	48"		
Ramp(s)	16" Extension, 4000 lb. with Assist		
Side Door	48" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Roof Vent Frame, Sidewall Airflow		
Fenders	Extruded Aluminum		
Axle	(2) 5200 lb. Torsion Brake, Spread Axle Configuration		
Hubs	Easy Lube		
Breakaway	Battery, Switch, and Lanyard		
Tires	ST225/75R15D 8-PR		
Wheels	15", 6-Hole Aluminum		
Exterior Finish	.030" Aluminum		
Undercoating	Automotive		
Exterior Fastening	VHB Bonded (Screwless)		
Exterior Trim	2.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop, Polished Cast Aluminum Roof Corners		
Stone Guard	24" ATP		
Rear Spoiler	9" Brite Aluminum Flare		
Roof	Flat Top Seamless Aluminum		
Roof Cap	Brite Aluminum		
Interior Walls	9mm White Vinyl		
Interior Trim	Extruded Aluminum Wall Transitions		
Ceiling	Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) 11" LED		
Switches	(1) Dome Light, 12V, (1) Load Light, 12V		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 28	8.5 x 30	8.5 x 32
Cargo Control	(4) 5000 lb. Recessed D-Rings		
Connector Plug	Round 7-pin Blade		
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights		
DIMENSIONS			
Overall Length	401"	425"	449"
Deck Length	331"	355"	379"
Deck Width	96.88"		
Deck Height	23.75"		